

# Direct



Application illustration only, subject lamps not used in photo.



## GE LED replacement lamps for HID-Ballast Bypass (Type B)

GE's LED replacement for HID lamps leverage the low energy and long life of LED.

The existing fixture is wired to bypass the ballast, which reduces energy use and eliminates the need to check ballast compatibility. Additional maintenance savings are realized by removing costs associated with purchasing and installing ballasts.

### LOW-COST OPERATION

- Uses 60% less energy, providing similar light output
- For example, an LED lamp using 150 watts, saves \$1,705 in energy costs over the rated life of the lamp vs. a standard 460 watt HID lamp system (400W lamp and 60W ballast) based on \$0.11 per kWh
- Ballast bypass (Type B) wiring eliminates costs associated with replacing ballasts
- Total system >140 LPW

### VERSATILE UPDATE

- Uses existing fixture optics
- Instant On/Brightness
- Flexible use - universal burn
- Rated for open and enclosed fixtures
- Temperature rating for -20°C to 50°C
- Exceeding temperature ratings will shorten life of lamp
- Type B eliminates the need to check ballast compatibility

### LONG LIFE

- 2.5X Longer Life (50,000 hr LED vs 20,000 hr HID)
- 50,000 hour rated life (L70)
- 50,000 hour rated fan life (B10)
- High-Performance fan ensures rated lamp life

### COLOR RENDERING

- Available with a CRI of 70

### COLOR TEMPERATURE

- Available in 4000K and 5000K

### ENVIRONMENTALLY CONSCIOUS

- These lamps are energy efficient and are compliant with material restriction requirements of RoHS

### GE QUALITY AND RELIABILITY

- 5-year limited warranty
- Tether Kit and in-line fuse included
- Robust construction with metal components
- Driver with internal fuse provides 6 kV surge protection

ecomagination<sup>SM</sup>

To learn more about saving money and energy, go to: <http://products.currentbyge.com>.

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

**current**  
powered by GE



## GE LED HID Type B Replacement Lamps

Bulb Shape	Base Type	Watts	Order Code	Description	Fixture Rating	Volts	Case Qty	MOL (in)	MOD (in)	Lumens Initial	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	#Location Rating	Additional Information	
LED Replacement Lamps for HID																		
	MED	50	22779	LED50ED23.5M/740	Open and Closed Rated	120-277	3	7.7	3.6	7,500	4000K	>70	100W	50,000	-	Damp	Coming Soon.	
		80	22768	LED80ED23.5M/740	Open and Closed Rated	120-277	3	7.7	3.6	12,000	4000K	>70	175W	50,000	-	Damp	Coming Soon.	
	EX39	50	22679	LED50ED23.5/740	Open and Closed Rated	120-277	3	7.7	3.6	7,500	4000K	>70	100W	50,000	-	Damp	Coming Soon.	
			22739	LED50ED23.5/750	Open and Closed Rated	120-277	3	7.7	3.6	7,500	5000K	>70	100W	50,000	-	Damp	Coming Soon.	
	80	22635	LED80ED23.5/740	Open and Closed Rated	120-277	3	7.7	3.6	12,000	4000K	>70	175W	50,000	-	Damp	Coming Soon.		
			22676	LED80ED23.5/750	Open and Closed Rated	120-277	3	7.7	3.6	12,000	5000K	>70	175W	50,000	-	Damp	Coming Soon.	
	115	22622	LED115ED28/740	Open and Closed Rated	120-277	3	8.3	4	18,000	4000K	>70	250W	50,000	-	Damp	Ballast bypass required.		
			22623	LED115ED28/750	Open and Closed Rated	120-277	3	8.3	4	18,000	5000K	>70	250W	50,000	-	Damp	Ballast bypass required.	
	150	22611	LED150ED28/740	Open and Closed Rated	120-277	3	8.3	4	23,500	4000K	>70	400W	50,000	-	Damp	Ballast bypass required.		
			22613	LED150ED28/750	Open and Closed Rated	120-277	3	8.3	4	23,500	5000K	>70	400W	50,000	-	Damp	Ballast bypass required.	

## Energy Savings switching from HID to LED Type B

Lamp Replacement Wattage	HID System Wattage	LED System Wattage	System Energy Savings	System Energy Cost Savings Over Life of Lamp*
400W	460W	150W	310W	\$1,705
250W	290W	115W	175W	\$962
175W	210W	80W	130W	\$715
100W	120W	50W	70W	\$385

\*Based on energy rates at .11kwh over the life of the lamp

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

\* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

\*\* Minimum order quantity = 1

# UL 1993 Environmental Requirements for LED LAMPS

- Location, damp – Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.
- Location, dry – Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.
- Location, wet – Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

ecomagination<sup>SM</sup>

current  
powered by GE

<http://products.currentbyge.com>.

GE and the GE Monogram are trademarks of the General Electric Company. All other trademarks are the property of their respective owners. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions. GE Lighting and GE Lighting Solutions, LLC are businesses of the General Electric Company. © 2017 GE.

LEDL051 (Rev 09/08/17)

