








# LED REPLACEMENT LAMPS

## Type A 4-pin Plug-In Lamps

Bulb Shape	Base Type	Lamp Watts	Order Code	Description	Case Qty <sup>2</sup>	MOL (In)	Lumens (Initial)	Color Temp (Initial)	CRI	Wattage Replacement	Rated Life L70 (Hrs) <sup>1</sup>	Dimmable	DLC <sup>4</sup>	Location Rating <sup>3</sup>	Additional Information <sup>*</sup>
<b>Vertical Type A 4-pin</b>															
<b>Plug-In</b>															
	G24q/GX24q	9	93300089	LED9G24q-V/8SC-4PK	24	5.9	1000 1100 1100 1100	2700K 3000K 3500K 4000K	80	13/18/26	50,000	-	-	Damp	SpectraChoice™ Selectable Color Temperature (4000K Default), Requires Electronic Ballast, Fully Enclosed, 4 pack
	G24q/GX24q	9	33956	LED9G24Q-V/827	6	5.9	1100	2700K	80	13/18/26	50,000	-	-	Damp	Requires Electronic Ballast, Fully Enclosed
	G24q/GX24q	9	33969	LED9G24Q-V/830	6	5.9	1200	3000K	80	13/18/26	50,000	-	-	Damp	Requires Electronic Ballast, Fully Enclosed
	G24q/GX24q	9	33974	LED9G24Q-V/835	6	5.9	1200	3500K	80	13/18/26	50,000	-	-	Damp	Requires Electronic Ballast, Fully Enclosed
	G24q/GX24q	9	33975	LED9G24Q-V/840	6	5.9	1200	4000K	80	13/18/26	50,000	-	-	Damp	Requires Electronic Ballast, Fully Enclosed
	GX24q	18.5	39288	LED19GX24q-V/827	6	6.42	1800	2700K	80	32/42	50,000	-	-	Damp	Requires Electronic Ballast
	GX24q	18.5	39277	LED19GX24q-V/830	6	6.42	1850	3000K	80	32/42	50,000	-	-	Damp	Requires Electronic Ballast
	GX24q	18.5	39275	LED19GX24q-V/835	6	6.42	1950	3500K	80	32/42	50,000	-	-	Damp	Requires Electronic Ballast
	GX24q	18.5	39279	LED19GX24q-V/840	6	6.42	1950	4000K	80	32/42	50,000	-	-	Damp	Requires Electronic Ballast
<b>Horizontal Type A 4-pin</b>															
<b>Plug-In</b>															
	G24q/GX24q	9	33994	LED9G24Q-H/827	6	5.31	1100	2700K	80	13/18/26	50,000	-	-	Damp	Requires Electronic Ballast, Fully Enclosed
	G24q/GX24q	9	33997	LED9G24Q-H/830	6	5.31	1200	3000K	80	13/18/26	50,000	-	-	Damp	Requires Electronic Ballast, Fully Enclosed
	G24q/GX24q	9	33998	LED9G24Q-H/835	6	5.31	1200	3500K	80	13/18/26	50,000	-	-	Damp	Requires Electronic Ballast, Fully Enclosed
	G24q/GX24q	9	33999	LED9G24Q-H/840	6	5.31	1200	4000K	80	13/18/26	50,000	-	-	Damp	Requires Electronic Ballast, Fully Enclosed
	GX24q	18.5	39289	LED19GX24q-H/827	6	6.7	1850	2700K	80	32/42	50,000	-	-	Damp	Requires Electronic Ballast
	GX24q	18.5	39282	LED19GX24q-H/830	6	6.7	1850	3000K	80	32/42	50,000	-	-	Damp	Requires Electronic Ballast
	GX24q	18.5	39276	LED19GX24q-H/835	6	6.7	1950	3500K	80	32/42	50,000	-	-	Damp	Requires Electronic Ballast
	GX24q	18.5	39283	LED19GX24q-H/840	6	6.7	1950	4000K	80	32/42	50,000	-	-	Damp	Requires Electronic Ballast


\* Check ballast compatibility at LED.com/LED4pin-compatibility

## Type A 2-pin Plug-In Lamps

Bulb Shape	Base Type	Lamp Watts	Order Code	Description	Case Qty <sup>2</sup>	MOL (In)	Lumens (Initial)	Color Temp (Initial)	CRI	Wattage Replacement	Rated Life L70 (Hrs) <sup>1</sup>	Dimmable	DLC <sup>4</sup>	Location Rating <sup>3</sup>	Additional Information <sup>*</sup>
<b>Type A GX23 2-pin</b>															
<b>Plug-In</b>															
	GX23	5	91404	LED5GX23/827	6	6.7	500	2700K	80	13	50,000	-	-	Damp	Requires Magnetic Ballast, Fully Enclosed
	GX23	5	91405	LED5GX23/830	6	6.7	530	3000K	80	13	50,000	-	-	Damp	Requires Magnetic Ballast, Fully Enclosed
	GX23	5	91407	LED5GX23/835	6	6.7	545	3500K	80	13	50,000	-	-	Damp	Requires Magnetic Ballast, Fully Enclosed
	GX23	5	91408	LED5GX23/840	6	6.7	560	4000K	80	13	50,000	-	-	Damp	Requires Magnetic Ballast, Fully Enclosed
	GX23	5	91410	LED5GX23/850	6	6.7	565	5000K	80	13	50,000	-	-	Damp	Requires Magnetic Ballast, Fully Enclosed
<b>Vertical Type A G24d 2-pin</b>															
<b>Plug-In</b>															
	G24d	10.5	93300091	LED11G24d-V/8SC-4PK	24	6.2	1000 1100 1100 1100	2700K 3000K 3500K 4000K	80	13/18/26	50,000	-	-	Damp	SpectraChoice™ Selectable Color Temperature (4000K Default), Requires Magnetic Ballast, Fully Enclosed, 4 pack
	G24d	10.5	92988	LED11G24d-V/835	6	6.2	1050	3500K	80	13/18/26	50,000	-	-	Damp	Requires Magnetic Ballast, Fully Enclosed
	G24d	10.5	92996	LED11G24d-V/840	6	6.2	1050	4000K	80	13/18/26	50,000	-	-	Damp	Requires Magnetic Ballast, Fully Enclosed
<b>Horizontal Type A G24d 2-Pin</b>															
<b>Plug-In</b>															
	G24d	10.5	93300090	LED11G24d-H/8SC-4PK	24	6.6	1000 1100 1100 1100	2700K 3000K 3500K 4000K	80	13/18/26	50,000	-	-	Damp	SpectraChoice™ Selectable Color Temperature (4000K Default), Requires Magnetic Ballast, Fully Enclosed, 4 pack
	G24d	10.5	92994	LED11G24d-H/827	6	6.6	1000	2700K	80	13/18/26	50,000	-	-	Damp	Requires Magnetic Ballast, Fully Enclosed
	G24d	10.5	92993	LED11G24d-H/830	6	6.6	1050	3000K	80	13/18/26	50,000	-	-	Damp	Requires Magnetic Ballast, Fully Enclosed
	G24d	10.5	92990	LED11G24d-H/835	6	6.6	1050	3500K	80	13/18/26	50,000	-	-	Damp	Requires Magnetic Ballast, Fully Enclosed
	G24d	10.5	92992	LED11G24d-H/840	6	6.6	1050	4000K	80	13/18/26	50,000	-	-	Damp	Requires Magnetic Ballast, Fully Enclosed

\* Check ballast compatibility at LED.com/LED2pin-compatibility

## Type A High Lumen Biax 2G11 Plug-In Lamps

Bulb Shape	Base Type	Lamp Watts	Order Code	Description	Case Qty <sup>2</sup>	MOL (In)	Lumens (Initial)	Color Temp (Initial)	CRI	Wattage Replacement	Rated Life L70 (Hrs) <sup>1</sup>	Dimmable	DLC <sup>4</sup>	Location Rating <sup>3</sup>	Additional Information <sup>*</sup>
<b>High Lumen Biax Type A (HLBX)</b>															
<b>HLBX</b>															
	2G11	17	39073	LED172G11/830/10	10	22.3	2150	3000K	80	40	50,000	-	-	Damp	Instant or PRS Ballast
	2G11	17	39074	LED172G11/835/10	10	22.3	2150	3500K	80	40	50,000	-	-	Damp	Instant or PRS Ballast
	2G11	17	39075	LED172G11/840/10	10	22.3	2200	4000K	80	40	50,000	-	-	Damp	Instant or PRS Ballast
	2G11	17	39076	LED172G11/850/10	10	22.3	2200	5000K	80	40	50,000	-	-	Damp	Instant or PRS Ballast

\* Check ballast compatibility at LED.com/LED2G11-compatibility

<sup>1</sup> The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original lumen output (L70)

<sup>2</sup> Minimum order quantity = Case Qty

<sup>3</sup> UL 1993 Environmental Requirements for LED LAMPS

Damp Location – Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to electrical equipment, including partially protected locations

Dry Location – Location not normally subject to dampness, but may include a location subject to temporary dampness (i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture)

Wet Location – Location in which water or other liquid can drip, splash, or flow on or against electrical equipment

<sup>4</sup> Not all product variations on this page are DLC qualified. Visit [qpl.designlights.org/solid-state-lighting](http://qpl.designlights.org/solid-state-lighting) to confirm qualification.

Updated / New Product

Information provided is subject to change without notice. Please verify all details with Current. All values are design or typical values when measured under laboratory conditions, and Current makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

Get more information at  
[www.LED.com](http://www.LED.com)