

naturalLED®

Turning Light into Savings ▶▶▶



BR, R

8W, 9W, 11W, 12W, 13W, 14W, 17W, 18W

With a full array of R and BR lamps, naturalLED® offer various replacement for incandescent lamps. Direct replacement lamps for your decorative lighting, which is free of mercury and lead, UL listed and dimmability functions.

Our BR lamps available in standard medium base (E26), offering in 7 watt to 18 watt replacing up to 120 watt incandescent lamps. Our BR30 and BR40 are available for an excellent CRI90 meeting your lighting needs.

naturalLED® lamps are ideal lighting solution for track lights, display lights, hotel boutiques, residential, retail, museum lighting and any hospitality applications.



Key Features & Benefits

- ▶ Direct replacement and Instant On
- ▶ Up to 84% energy savings
- ▶ Contains no mercury or lead
- ▶ UL/cUL Listed
- ▶ Rated 15,000~25,000 hours average life
- ▶ 3 Years Limited Warranty

Applications

- ▶ Display Case Lighting
- ▶ Recessed Downlight
- ▶ Accent Lighting
- ▶ General Lighting
- ▶ Residential Lighting
- ▶ Restaurant Lighting


Color Choices



White

Qualifications



Item Code	Description	Bulbs	Color Temp	Wattage	Lumen Output	Equivalent Wattage	CRI	Voltage	Beam Angle	Rated Hours	Dimmable	
R20												
R20	5834	LED8R20/50L/927	R20	2700K	8	500	50	>90	120V	R20	25,000	• •
	5982	LED8R20/52L/950	R20	5000K	8	520	50	>90	120V	R20	25,000	• •
BR30												
BR30	5835	LED9BR30/65L/927	BR30	2700K	9	650	65	>90	120V	BR30	25,000	• •
	5983	LED9BR30/71L/950	BR30	5000K	9	710	65	>90	120V	BR30	25,000	• •
	5842	LED12BR30/90L/927	BR30	2700K	12	900	75	>90	120V	BR30	25,000	• •
	5978	LED12BR30/90L/940	BR30	4000K	12	900	75	>90	120V	BR30	25,000	• •
	5984	LED12BR30/95L/950	BR30	5000K	12	950	75	>90	120V	BR30	25,000	• •
	5783	LED11BR30/85L/27K	BR30	2700K	11	850	65	>80	120V	BR30	25,000	•
	5841	LED11BR30/85L/50K	BR30	5000K	11	850	65	>80	120V	BR30	25,000	•
	5894	LED12BR30/80L/927	BR30	2700K	12	800	65	>90	120V	BR30	25,000	•
BR30 (Twin pack)												
	5886	LED8BR30/65L/827CP	BR30	2700K	8	610	50	>80	120V	BR30	25,000	•
BR / R 40												
BR / R 40	5986	LED14BR40/100L/930	BR40	2700K	14	1,000	90	>90	120V	BR30	25,000	• •
	5836	LED15BR40/120L/927	BR40	5000K	15	1,200	90	>90	120V	BR30	25,000	• •
	5985	LED15BR40/130L/950	BR40	2700K	15	1,300	90	>90	120V	BR30	25,000	• •
	5895	LED12BR40/105L/827	BR40	4000K	12	1,050	75	>80	120V	BR30	25,000	•
	5816	LLED13BR40/105L/27K	BR40	5000K	13	1,050	70	>80	120V	BR30	25,000	•
	5896	LED14BR40/100L/927	BR40	2700K	14	1,000	75	>90	120V	BR30	25,000	•
	5784	LED17BR40/140L/27K	BR40	5000K	17	1,400	100	>80	120V	BR30	25,000	•
	5707	LH013R40/DIM/30K	R40	2700K	13	880	80	>80	120V	BR30	25,000	•
5724	LH018R40/DIM/30K	R40	5000K	18	1,230	120	>80	120V	BR30	25,000	•	

► Dimensions

<p>BR40 BR30 R20</p>	Item	A	B		Weight (lbs)
	R20	2.50-in	3.80-in	--	0.14
	BR30	3.70-in	5.00-in	--	0.35
	BR40	4.50-in	6.40-in	--	0.57

► Master Carton Package

