



## TECHNICAL SPECIFICATION SHEET

### Filaments

14W LED A19 3000K FILAMENT CLEAR E26 FULLY COMPATIBLE DIMMING

Item# 776916

Ordering Code LED14A19/30K/FIL/3

UPC 739698819693

- A19 LED bulb with an E26, medium screw, base in a Clear finish.
- 100 Watt equivalent, using only 14 Watts (1600 lumens).
- 3000K color temperature for a Soft White light.
- Fully Dimmable and works with most dimmer switches.
- Wet Rated for use in indoor / outdoor (can be exposed to water) locations.
- Long lasting energy efficient LED lighting, lasts up to 15,000 hours.
- 5 year Limited Lifetime Warranty



Width	Height	Length
2.48 in	4.53 in	2.48 in



Technical Specifications			
Avg Hours	15000	Inner Carton UPC	10739698819690
Base	E26	Item #	776916
Beam Angle(°)	320°	Lumens	1600
Bulb Type	A19	M.O.D	2.36 in
CBCP	0	M.O.L	4.13 in
CCT Color	3000K	Max Op Temp	40 C
Color	Soft White Light	Min Op Temp	-20 C
CRI	90	Outer Carton Qty	1
Dimmable	Y	Outer Carton UPC	40739698819691
Enclosed Rated	Y	Safety Rated	UL
Energy Star	N	Safety Rating Type	WET
Equivalent	100	Title 20	Y
Finish	Clear	Title 24	N
Individual Qty	1	Volts	120
Individual UPC	739698819693	Warranty Years	5
Inner Carton Qty	10	Watts	14



100 West Commercial Ave  
Morristown, NJ 07960

### Dimmer Compatibility Guide

PLEASE NOTE: Compatibility list is based upon testing conducted by the manufacturer in a lab controlled environment. Actual results may vary.

<b>Product Family Name:</b>	776915	776916	776918	776919
<b>Item Number:</b>	LED14A19/27K/FL/3	LED14A19/30K/FL/3	LED14A19/27K/FL/M/3	LED14A19/30K/FL/M/3
<b>Ordering Code:</b>				
<b>Item Number:</b>				
<b>Ordering Code:</b>				

Manufacturer	Product	Model Number	Overall Rating	Lamps per Dimmer		Notes	
				Recommended Minimum	Maximum Tested*		
Incandescent/Halogen (Triac/Phase Cut/Leading Edge Dimmers)	Lumatech	SureSlide	IP66	Best	1	6	Dim down to 1%
		SureSlide	6613-P	Best	1	6	Dim down to 1%
	Vizia	Toggle	VPS6-SL2	Good	2	6	Dim down to 1%
		Toggle	TG-600	Best	1	6	Dim down to 1%
	Lutron	Decora	DCL-600	Best	1	6	Dim down to 1%
		Dina	DW-600	Best	1	6	Dim down to 1%
	Lagrand	SkyLark	S-600	Best	1	6	Dim down to 1%
		Maestro	MAW-600	Good	2	6	Dim down to 1%
		Titan	CD703-PW	Best	1	6	Dim down to 1%
		Harmony	D703-PTC	Best	1	6	Dim down to 1%
CFL/LED	Lumatech	IP66	Best	1	6	Dim down to 1%	
		6674	Best	1	6	Dim down to 4%	
	Decora	6672	Best	1	6	Dim down to 3%	
		Decora Slide	DCL6-SL2	Best	1	6	Dim down to 3%
	Lutron	SkyLark	CTCL-133	Best	1	6	Dim down to 1%
		Sunista	STCL-133	Best	1	6	Dim down to 1%
	Lagrand	Dina	DWCL-153PL	Best	1	6	Dim down to 1%
		Maestro	MACL-153MLH	Best	1	6	Dim down to 1%
		SkyLark	SCL-153P	Best	1	6	Dim down to 1%
		Toggle	TGCL-153PH	Best	1	6	Dim down to 1%
Radio RA	RA288-GCL-PD	Best	1	6	Dim down to 1%		
	Harmony	DCL453-PTC	Best	1	6	Dim down to 1%	
Adorne Paddle	RHCL453PW	Best	1	6	Dim down to 1%		
	ADPD453LM2	Good	1	6	Dim down to 20%		
Electronic Low Voltage	Lumatech	VPS04	Best	1	6	Dim down to 4%	
		IP604	Good	1	6	Dim down to 2%, not smooth dimming	
	Decora	6615-P	Good	1	6	Dim down to 3%	
		SkyLark Countour	CTELV-300P	Best	1	6	Dim down to 3%
	Lutron	Dina	DWELV-300P	Best	1	6	Dim down to 3%
		Maestro	MAELV-600	Best	1	6	Dim down to 3%
	Lagrand	SkyLark	SELV-300P	Best	1	6	Dim down to 3%
		NEBT	VTBL-600M-W	Best	1	6	Dim down to 3%
	Scene Director	SELV	Good	1	6	Dim down to 12%	
	Magnetic Low Voltage	Lumatech	VPM-05	Good	2	6	Dim down to 2%
6613-P			Best	1	6	Dim down to 1%	
Lutron		Maestro	MALV-600	Not compatible	1	6	Not turn on with 1-6
		Harmony	DLV703-PW	Best	1	6	Dim down to 1%
Titan	CDLV703-PW	Best	1	6	Dim down to 5%		
Smart Dimmer	Lumatech	Decora Digital (Bluetooth)	DDRX1-6L2	Best	1	6	Dim down to 4%
		Decora Smart 2-Wave Technology	DS2HD	Best	1	6	Dim down to 4%
	Lutron	Decora Smart WiFi Technology	DW1KD	Best	1	6	Dim down to 4%
		Caseta Wireless smart dimmer Wi-Fi	PD-32AKD	Best	1	6	Dim down to 3%
	GE	Caseta Wireless smart dimmer Wi-Fi	PD-6WCL	Best	1	6	Dim down to 2%
		2-WAVE	DW3005	Best	1	6	Dim down to 1%
Universal	Lagrand	Adorne SoftTap	ADPT703TU	Good	1	6	Dim down to 15%
		Mira Decorator	DRD4-W	Best	1	6	Dim down to 1%
		Harmony	H703PTUTC	Bad	1	6	Dim down to 25%
	Cooper	Adorne Whisper	ADWR703MMTUW2	Best	1	6	Dim down to 1%
		Adorne Touch	ADTH703MMTUW2	Best	1	6	Dim down to 1%
		Decorator	SAU09-C2-4-L	Best	1	6	Dim down to 1%
Shye	SAU09-W-4-L	Best	1	6	Dim down to 1%		

\*Maximum Tested (Lamps per Dimmer) - Additional lamps may work with your dimmer system. For maximum capacity please consult dimmer manufacturer.  
 \*May experience "pop-on", lights cannot be turned on immediately to their minimum level. The slider needs to be raised above the minimum light level for the lights to first turn on if they were initially off. Then, the slider can be lowered to get to a lower light level; the dimmer cannot be turned on to just the minimum level.

**Overall Rating**

**Not Compatible** One or more of the following observed: Major flickering at various points, significant audible noise, no dimming range, does not turn off.

**Bad** One or more of the following observed: Some flickering observed at various points, audible noise may be present, dimming not smooth.

**Good** One or more of the following observed: Minor flickering at some point may exist. Dead travel may exist, which means there may be periods of time when the slider (or other form of control button) is moved without affecting the light level. These periods of dead travel are minor and most of the time not visible. Minor audible noise.

**Best** Most of the following observed: No flickering, minimal audible noise (typically less than 25 dBA), wide dimming range - can dim down to 20% or less of light output.

**High End (H.E.) Dead Travel**

**Low End (L.E.) Dead Travel** Determines how much, if any, dead travel exists at the top and bottom of the dimmer's range. Dead travel is when the slider can be moved without affecting the light level.

©2015 Bulbrite Inc.  
 Bulbrite Industries Inc.  
 100 West Commercial Avenue  
 Morristown, New Jersey 07960  
 P.O. Box 1, 800-528-0100  
 Fax: 908-880-0108  
 Email: ProductSupport@bulbrite.com  
 www.bulbrite.com