PRODUCT DATASHEET
TruWave® A19 15W DIM FR 5000K 4PK

SYLVANIA TruWave® A19/A21 Lamps | TruWave A19/A21 LED lamps with natural light, 90+ CRI, and reduced blue light



Areas of application

- Downlights, pendant fixtures, table lamps, wall sconces
- Healthcare, hospitality, residential, retail

Product features

- Controls blue wavelengths for lower glare and reduced eye strain to improve readability
- Supports an improved sleep-wake cycle
- Clean light color rendering for seeing realistic, vivid colors
- Exceptional color quality without the loss of efficacy typical of most 90+ CRI solutions
- Properly saturates red to make building spaces and flesh tones accurate and vibrant
- 15,000 hours lifetime (L70)
- CRI 90+ for exceptional color quality
- Dimmable down to 10 %
- Approved for enclosed fixtures

© 2026, LEDVANCE GmbH. All rights reserved.

TECHNICAL DATA

Additional product data

Base type	E26
Mercury content	0.0 mg
Ordering Abbreviation	LED15A19DIMO95013YTLRP4
Abbrev. With Packaging Info.	LED15A19DIMO95013YTLRP4 16/CS 4/SKU
SKU UPC	0046135422768
NAED	42276
Family Brand Name	TruWave™
General Description	LED TruWave™ A19, 15W Equivalent, 1600 Lumens, 5000K, 90CRI, 15, 000Hours Life, E26 Medium, Frosted Finish
Warranty	3 years

Electrical data

Nominal Wattage	15.00 W
Nominal voltage	120.00 V
Claimed Equivalent Lamp Pwr	100 W

Photometrical data

Lumens	1600 lm
Efficacy	139
Color Temperature/CCT	5000 K
Color Rendering Index (CRI)	90
Light color	950

Dimensions & Weight

Overall length	104.00 mm
Diameter	2.36 in
Product weight	0.08 lb

Materials & Colors

Lamp Finish	Frosted
Bulb shape	A19
Bulb Glass Type	SOFT GLASS

Application & Mounting

Dimming	Yes

Lifespan

Average Rated Life (hr)	15000

© 2026, LEDVANCE GmbH. All rights reserved.

Capabilities

Dimming	Yes

Certificates & Standards

Certification Listing	RoHS / CSA / FTC / FCC / CEC

Logistical data

SKU Qty	4
Case Qty	16
Case Length (in)	10.438
Case Width (in)	5.125
Case Depth (in)	7.375
Case Cube (ft)	0.228
Case Weight (lbs)	1.425
SKU UPC	0046135422768
Pallet Qty	2,976

Safety advice

- Suitable for damp locations.
- Approved for use in enclosed fixtures.
- -4°F to +113°F (-20°C to +45°C)

DOWNLOAD DATA

	Spec Sheets and Product Documents	Document name
PDF	Product Family Spec Sheet	LED537 TruWave Technology A19

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2026, LEDVANCE GmbH. All rights reserved.