



LED Lamps - Directional



LED PAR Lamps

Current offers LED PAR lamps featuring the exclusive Visual Comfort Lens design. With advanced optics and reduced glare, these lamps offer the light qualities desired by merchants for retail applications. High output and value lines are also available to serve applications needing higher lumens or when advanced optics are not required.

PERFORMANCE HIGHLIGHTS:

| PAR Lamps | |
|----------------------------|------------------------------------|
| Light Output: | 430-3100 Lumens |
| CRI: | 80-92 |
| CCT: | 2700K, 3000K, 3500K, 4000K & 5000K |
| Efficiency | Up to 79 LPW |
| Wattage: | 7W, 12W, 15W, 18W, 32W |
| Life: | Up to 25,000 hours L70 |
| Temperature Rating: | -20° to 45° C |
| Rating: | Damp or Wet |
| Dimming: | Dims from 100% to 10% |

FEATURES:

- Halogen-like color
- Available in different beam patterns
- These lamps are energy efficient, contain no lead or mercury, and are compliant with material restriction requirements of RoHS

BENEFITS:

- Energy + Cost Savings
- Our LED PAR lamps have less heat, UV or infrared in the beam, which reduces the potential for fading of materials and décor, compared to halogen or incandescent lamps
- Energy efficiency and long life mean fewer lamp replacements versus standard incandescent or halogen light sources
- Title 20 compliant options

LIMITED WARRANTY

3 Years

LEARN MORE:

To learn more about saving money and energy, go to www.LED.com.



Product is compliant with material restriction requirements of RoHS. ENERGY STAR® is a registered U.S. mark



LED Lamps - Directional

LED PAR Lamps

CUSTOMER NAME _____
 PROJECT NAME _____
 DATE _____ NOTES _____

Directional Lamps (PAR16 - PAR20)

| Bulb Shape | Base Type | Watts | Order Code | Description | Volts | Carton Qty ² | MOL (in) | Lumens (Initial) | CBCP | Color Temp. (Initial) | CRI | Wattage Replacement | Rated Life L70 (Hrs) ¹ | Dimmable | ENERGY STAR ³ Status | Location Rating ³ | Beam Angle | Housing Color | Additional Information |
|----------------------|-----------|-------|------------|---------------------|-------|-------------------------|----------|------------------|------|-----------------------|-----|---------------------|-----------------------------------|----------|---------------------------------|------------------------------|------------|---------------|------------------------|
| Compact PAR16 | | | | | | | | | | | | | | | | | | | |
| PAR16 | E26 | 6 | 93305603 | LED6DP16W830/35-6PK | 120 | 24 | 3.0 | 550 | 1000 | 3000K | 80 | 60 | 25,000 | Yes | ★ | Damp | 35° | White | 6 pack |
| Compact PAR20 | | | | | | | | | | | | | | | | | | | |
| PAR20 | E26 | 7 | 93349 | LED7DP203B827/20 | 120 | 6 | 3.5 | 500 | 3600 | 2700K | 80 | 50 | 25,000 | Yes | ★ | Damp | 20° | Black | |
| | E26 | 7 | 93360 | LED7DP203W827/20 | 120 | 6 | 3.5 | 500 | 3600 | 2700K | 80 | 50 | 25,000 | Yes | ★ | Damp | 20° | White | |
| | E26 | 7 | 93311901 | LED7DP20OB927/35 | 120 | 6 | 3.5 | 500 | 966 | 2700K | 90 | 50 | 25,000 | Yes | - | Wet | 35° | Black | CEC Title 20 |
| | E26 | 7 | 93354 | LED7DP203B827/35 | 120 | 6 | 3.5 | 500 | 1150 | 2700K | 80 | 50 | 25,000 | Yes | ★ | Damp | 35° | Black | |
| | E26 | 7 | 93107782 | LED7DP203W927/35 | 120 | 6 | 3.5 | 430 | 1000 | 2700K | 90 | 50 | 25,000 | Yes | - | Damp | 35° | White | |
| | E26 | 7 | 93311900 | LED7DP20OW927/35 | 120 | 6 | 3.5 | 500 | 966 | 2700K | 90 | 50 | 25,000 | Yes | - | Wet | 35° | White | CEC Title 20 |
| | E26 | 7 | 93362 | LED7DP203W827/35 | 120 | 6 | 3.5 | 500 | 1150 | 2700K | 80 | 50 | 25,000 | Yes | ★ | Damp | 35° | White | |
| | E26 | 7 | 93327 | LED7DP203B830/20 | 120 | 6 | 3.5 | 520 | 3600 | 3000K | 80 | 50 | 25,000 | Yes | ★ | Damp | 20° | Black | |
| | E26 | 7 | 93347 | LED7DP203W830/20 | 120 | 6 | 3.5 | 520 | 3600 | 3000K | 80 | 50 | 25,000 | Yes | ★ | Damp | 20° | White | |
| | E26 | 7 | 93311903 | LED7DP20OB930/35 | 120 | 6 | 3.5 | 520 | 966 | 3000K | 90 | 50 | 25,000 | Yes | - | Wet | 35° | Black | CEC Title 20 |
| | E26 | 7 | 93311902 | LED7DP20OW930/35 | 120 | 6 | 3.5 | 520 | 966 | 3000K | 90 | 50 | 25,000 | Yes | - | Wet | 35° | White | CEC Title 20 |



Directional Lamps (PAR30 - Visual Comfort Lens)

| Bulb Shape | Base Type | Watts | Order Code | Description | Volts | Carton Qty ² | MOL (in) | Lumens (Initial) | CBCP | Color Temp. (Initial) | CRI | Wattage Replacement | Rated Life L70 (Hrs) ¹ | Dimmable | ENERGY STAR ³ Status | Location Rating ³ | Beam Angle | Housing Color | Additional Information |
|--|-----------|-------|------------|--------------------|-------|-------------------------|----------|------------------|------|-----------------------|-----|---------------------|-----------------------------------|----------|---------------------------------|------------------------------|------------|---------------|------------------------|
| PAR30 - Low Glare - Visual Comfort Lens | | | | | | | | | | | | | | | | | | | |
| PAR30 | E26 | 12 | 93311923 | LED12DP30RW927/25 | 120 | 6 | 3.6 | 1050 | 3800 | 2700K | 90 | 75 | 25,000 | Yes | ★ | Damp | 25° | White | CEC Title 20 |
| | E26 | 12 | 42133 | LED12DP30RW827/25 | 120 | 6 | 3.74 | 1000 | 4700 | 2700K | 80 | 75 | 25,000 | Yes | ★ | Damp | 25° | White | |
| | E26 | 12 | 93311925 | LED12DP30RB927/40 | 120 | 6 | 3.6 | 1050 | 2200 | 2700K | 90 | 75 | 25,000 | Yes | ★ | Damp | 40° | Black | CEC Title 20 |
| | E26 | 12 | 93107784 | LED12DP30RB927/40 | 120 | 6 | 3.74 | 850 | 1700 | 2700K | 90 | 75 | 25,000 | Yes | - | Damp | 40° | Black | |
| | E26 | 12 | 84395 | LED12DP30RW927/40 | 120 | 6 | 3.74 | 850 | 1700 | 2700K | 90 | 75 | 25,000 | Yes | ★ | Damp | 40° | White | |
| | E26 | 12 | 93311924 | LED12DP30RW927/40 | 120 | 6 | 3.6 | 1050 | 2200 | 2700K | 90 | 75 | 25,000 | Yes | ★ | Damp | 40° | White | CEC Title 20 |
| | E26 | 12 | 42134 | LED12DP30RW827/40 | 120 | 6 | 3.74 | 1000 | 2200 | 2700K | 80 | 75 | 25,000 | Yes | ★ | Damp | 40° | White | |
| | E26 | 12 | 93311926 | LED12DP30RW930/25 | 120 | 6 | 3.6 | 1050 | 3900 | 3000K | 90 | 75 | 25,000 | Yes | ★ | Damp | 25° | White | CEC Title 20 |
| | E26 | 12 | 84384 | LED12DP30RW830/25 | 120 | 6 | 3.74 | 1050 | 4800 | 3000K | 80 | 75 | 25,000 | Yes | ★ | Damp | 25° | White | |
| | E26 | 12 | 93311927 | LED12DP30RW930/40 | 120 | 6 | 3.6 | 1050 | 2200 | 3000K | 90 | 75 | 25,000 | Yes | ★ | Damp | 40° | White | CEC Title 20 |
| | E26 | 12 | 42131 | LED12DP30RW830/40 | 120 | 6 | 3.74 | 1050 | 2400 | 3000K | 80 | 75 | 25,000 | Yes | ★ | Damp | 40° | White | |
| PAR30 Long Neck - Low Glare - Visual Comfort Lens | | | | | | | | | | | | | | | | | | | |
| PAR30L | E26 | 12 | 93312005 | LED12DP30LRW927/25 | 120 | 6 | 4.7 | 1050 | 3800 | 2700K | 90 | 75 | 25,000 | Yes | ★ | Damp | 25° | White | CEC Title 20 |
| | E26 | 12 | 84407 | LED12DP30LRW927/40 | 120 | 6 | 4.72 | 850 | 1700 | 2700K | 90 | 75 | 25,000 | Yes | ★ | Damp | 40° | White | |
| | E26 | 12 | 93312006 | LED12DP30LRW927/40 | 120 | 6 | 4.7 | 1050 | 2200 | 2700K | 90 | 75 | 25,000 | Yes | ★ | Damp | 40° | White | CEC Title 20 |
| | E26 | 12 | 42144 | LED12DP30LRW827/40 | 120 | 6 | 4.72 | 1000 | 2200 | 2700K | 80 | 75 | 25,000 | Yes | ★ | Damp | 40° | White | |
| | E26 | 12 | 84399 | LED12DP30LRW930/25 | 120 | 6 | 4.72 | 900 | 3900 | 3000K | 90 | 75 | 25,000 | Yes | ★ | Damp | 25° | White | |
| | E26 | 12 | 93312007 | LED12DP30LRW930/25 | 120 | 6 | 4.7 | 1050 | 3900 | 3000K | 90 | 75 | 25,000 | Yes | ★ | Damp | 25° | White | CEC Title 20 |
| | E26 | 12 | 93312008 | LED12DP30LRW930/40 | 120 | 6 | 4.7 | 1050 | 2200 | 3000K | 90 | 75 | 25,000 | Yes | ★ | Damp | 40° | White | CEC Title 20 |
| | E26 | 12 | 42137 | LED12DP30LRW830/40 | 120 | 6 | 4.72 | 1050 | 2400 | 3000K | 80 | 75 | 25,000 | Yes | ★ | Damp | 40° | White | |



Directional Lamps (PAR30 - Value)

| Bulb Shape | Base Type | Watts | Order Code | Description | Volts | Carton Qty ² | MOL (in) | Lumens (Initial) | CBCP | Color Temp. (Initial) | CRI | Wattage Replacement | Rated Life L70 (Hrs) ¹ | Dimmable | ENERGY STAR ³ Status | Location Rating ³ | Beam Angle | Housing Color | Additional Information |
|-----------------------------------|-----------|-------|------------|-------------------------|-------|-------------------------|----------|------------------|------|-----------------------|-----|---------------------|-----------------------------------|----------|---------------------------------|------------------------------|------------|---------------|------------------------|
| PAR30 - TIR Lens | | | | | | | | | | | | | | | | | | | |
| PAR30 | E26 | 12 | 93153892 | LED12DP30VOW830/25-4PK | 120 | 16 | 3.66 | 850 | 3400 | 3000K | 80 | 75 | 15,000 | Yes | - | Wet | 25° | White | 4 pack |
| PAR30 Long Neck - TIR Lens | | | | | | | | | | | | | | | | | | | |
| PAR30L | E26 | 12 | 93153891 | LED12DP30LVOW830/25-4PK | 120 | 16 | 4.69 | 850 | 3400 | 3000K | 80 | 75 | 15,000 | Yes | - | Wet | 25° | White | 4 pack |

¹ The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original lumen output (L70)

² Minimum order quantity = Carton Qty

³ ENERGY STAR³ status: ENERGY STAR³ certified. Lamps without a "★" are not ENERGY STAR³ certified.

³ UL 1993 Environmental Requirements for LED LAMPS

Damp Location - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to electrical equipment, including partially protected locations

Wet Location - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment

When installing outdoors, ensure the socket used is suitably Listed for use in Wet locations and socket gaskets provided by the manufacturer are correctly attached.




LED Lamps - Directional

LED PAR Lamps

CUSTOMER NAME _____
 PROJECT NAME _____
 DATE _____ NOTES _____

Directional Lamps (PAR30 - High Output)

| Bulb Shape | Base Type | Watts | Order Code | Description | Volts | Carton Qty ² | MOL (in) | Lumens (Initial) | CBCP | Color Temp. (Initial) | CRI | Wattage Replacement | Rated Life L70 (Hrs) ¹ | Dimmable | ENERGY STAR ³ Status | Location Rating ³ | Beam Angle | Housing Color | Additional Information |
|--|-----------|-------|------------|-----------------|---------|-------------------------|----------|------------------|-------|-----------------------|-----|---------------------|-----------------------------------|----------|---------------------------------|------------------------------|------------|---------------|------------------------|
| PAR 30 Long Neck - High Output - Universal 120-277V | | | | | | | | | | | | | | | | | | | |
|  | E26 | 18 | 75089 | LED18P30LW83015 | 120-277 | 6 | 4.6 | 1800 | 15500 | 3000K | 80 | 75 | 25,000 | - | ★ | Damp | 15° | White | |
| | E26 | 18 | 75091 | LED18P30LW83025 | 120-277 | 6 | 4.6 | 1800 | 7000 | 3000K | 80 | 75 | 25,000 | - | ★ | Damp | 25° | White | |
| | E26 | 18 | 75065 | LED18P30LW93015 | 120-277 | 6 | 4.6 | 1400 | 12500 | 3000K | 90 | 75 | 25,000 | - | ★ | Damp | 15° | White | |
| | E26 | 18 | 75078 | LED18P30LW93025 | 120-277 | 6 | 4.6 | 1400 | 5000 | 3000K | 90 | 75 | 25,000 | - | ★ | Damp | 25° | White | |

Directional Lamps (PAR38 - Visual Comfort Lens)

| Bulb Shape | Base Type | Watts | Order Code | Description | Volts | Carton Qty ² | MOL (in) | Lumens (Initial) | CBCP | Color Temp. (Initial) | CRI | Wattage Replacement | Rated Life L70 (Hrs) ¹ | Dimmable | ENERGY STAR ³ Status | Location Rating ³ | Beam Angle | Housing Color | Additional Information |
|--|-----------|-------|------------|--------------------|-------|-------------------------|----------|------------------|-------|-----------------------|-----|---------------------|-----------------------------------|----------|---------------------------------|------------------------------|------------|---------------|------------------------|
| PAR38 - Low Glare - Visual Comfort Lens | | | | | | | | | | | | | | | | | | | |
| | E26 | 12 | 93311944 | LED12DP38ROW927/25 | 120 | 6 | 5.2 | 1050 | 5400 | 2700K | 90 | 100 | 25,000 | Yes | ★ | Wet | 25° | White | CEC Title 20 |
| | E26 | 12 | 93311945 | LED12DP38ROW927/40 | 120 | 6 | 5.2 | 1050 | 2300 | 2700K | 90 | 100 | 25,000 | Yes | ★ | Wet | 40° | White | CEC Title 20 |
| | E26 | 12 | 92971 | LED12D38W3827/40 | 120 | 6 | 5.31 | 1050 | 2300 | 2700K | 81 | 100 | 25,000 | Yes | ★ | Damp | 40° | White | |
| | E26 | 12 | 93311946 | LED12DP38ROW930/25 | 120 | 6 | 5.2 | 1050 | 5400 | 3000K | 90 | 100 | 25,000 | Yes | ★ | Wet | 25° | White | CEC Title 20 |
| | E26 | 12 | 92972 | LED12D38W3830/25 | 120 | 6 | 5.31 | 1050 | 5500 | 3000K | 81 | 100 | 25,000 | Yes | ★ | Damp | 25° | White | |
| | E26 | 12 | 93311947 | LED12DP38ROW930/40 | 120 | 6 | 5.2 | 1050 | 2300 | 3000K | 90 | 100 | 25,000 | Yes | ★ | Wet | 40° | White | CEC Title 20 |
| | E26 | 12 | 92973 | LED12D38OW3830/40 | 120 | 6 | 5.31 | 1050 | 2300 | 3000K | 80 | 100 | 25,000 | Yes | ★ | Wet | 40° | White | |
| | E26 | 16 | 93313077 | LED16DP38ROW930/15 | 120 | 6 | 5.2 | 1550 | 15000 | 3000K | 90 | 120 | 25,000 | Yes | - | Wet | 15° | White | CEC Title 20 |
| | E26 | 16 | 93313079 | LED16DP38ROW830/15 | 120 | 6 | 5.2 | 1800 | 18000 | 3000K | 80 | 120 | 25,000 | Yes | - | Wet | 15° | White | |
| | E26 | 16 | 93313081 | LED16DP38ROS830/15 | 120 | 6 | 5.2 | 1800 | 18000 | 3000K | 80 | 120 | 25,000 | Yes | - | Wet | 15° | Silver | |
| | E26 | 18 | 92923 | LED18D38W3927/25 | 120 | 6 | 5.31 | 1250 | 4900 | 2700K | 92 | 100 | 25,000 | Yes | ★ | Damp | 25° | White | |
| | E26 | 18 | 93311929 | LED18DP38ROW927/25 | 120 | 6 | 5.2 | 1550 | 5800 | 2700K | 90 | 120 | 25,000 | Yes | ★ | Wet | 25° | White | CEC Title 20 |
| | E26 | 18 | 92950 | LED18D38OW3827/25 | 120 | 6 | 5.31 | 1550 | 5800 | 2700K | 81 | 120 | 25,000 | Yes | ★ | Wet | 25° | White | |
| | E26 | 18 | 93311930 | LED18DP38ROW927/40 | 120 | 6 | 5.2 | 1550 | 3700 | 2700K | 90 | 150 | 25,000 | Yes | ★ | Wet | 40° | White | CEC Title 20 |
| | E26 | 18 | 92958 | LED18D38OW3827/40 | 120 | 6 | 5.31 | 1550 | 3800 | 2700K | 81 | 120 | 25,000 | Yes | ★ | Wet | 40° | White | |
| | E26 | 18 | 92961 | LED18D38W3830/15 | 120 | 6 | 5.31 | 1750 | 20000 | 3000K | 81 | 150 | 25,000 | Yes | ★ | Damp | 15° | White | |
| | E26 | 18 | 93096546 | LED18D38S3830/15 | 120 | 6 | 5.31 | 1750 | 20000 | 3000K | 80 | 150 | 25,000 | Yes | - | Damp | 15° | Silver | |
| | E26 | 18 | 93311932 | LED18DP38ROB930/25 | 120 | 6 | 5.2 | 1550 | 6000 | 3000K | 90 | 120 | 25,000 | Yes | ★ | Wet | 25° | Black | CEC Title 20 |
| | E26 | 18 | 93311931 | LED18DP38ROW930/25 | 120 | 6 | 5.2 | 1550 | 6000 | 3000K | 90 | 120 | 25,000 | Yes | ★ | Wet | 25° | White | CEC Title 20 |
| | E26 | 18 | 92963 | LED18D38OW3830/25 | 120 | 6 | 5.31 | 1550 | 6000 | 3000K | 81 | 120 | 25,000 | Yes | ★ | Wet | 25° | White | |
| | E26 | 18 | 93311933 | LED18DP38ROS930/25 | 120 | 6 | 5.2 | 1550 | 6000 | 3000K | 90 | 120 | 25,000 | Yes | ★ | Wet | 25° | Silver | CEC Title 20 |
| | E26 | 18 | 92934 | LED18D38W3930/40 | 120 | 6 | 5.31 | 1350 | 3200 | 3000K | 92 | 120 | 25,000 | Yes | ★ | Damp | 40° | White | |
| | E26 | 18 | 93311934 | LED18DP38ROW930/40 | 120 | 6 | 5.2 | 1550 | 3800 | 3000K | 90 | 150 | 25,000 | Yes | ★ | Wet | 40° | White | CEC Title 20 |
| | E26 | 18 | 92967 | LED18D38OW3830/40 | 120 | 6 | 5.31 | 1550 | 4000 | 3000K | 81 | 150 | 25,000 | Yes | ★ | Wet | 40° | White | |
| | E26 | 18 | 93311935 | LED18DP38ROW935/25 | 120 | 6 | 5.2 | 1700 | 6500 | 3500K | 90 | 120 | 25,000 | Yes | ★ | Wet | 25° | White | CEC Title 20 |
| | E26 | 18 | 85085 | LED18D38OW3835/25 | 120 | 6 | 5.31 | 1700 | 6500 | 3500K | 81 | 120 | 25,000 | Yes | ★ | Wet | 25° | White | |
| | E26 | 18 | 93311936 | LED18DP38ROW935/40 | 120 | 6 | 5.2 | 1700 | 4200 | 3500K | 90 | 150 | 25,000 | Yes | ★ | Wet | 40° | White | CEC Title 20 |
| | E26 | 18 | 87917 | LED18D38OW3835/40 | 120 | 6 | 5.31 | 1700 | 4400 | 3500K | 81 | 150 | 25,000 | Yes | ★ | Wet | 40° | White | |
| | E26 | 18 | 93311937 | LED18DP38ROW940/25 | 120 | 6 | 5.2 | 1700 | 6500 | 4000K | 90 | 120 | 25,000 | Yes | ★ | Wet | 25° | White | CEC Title 20 |
| | E26 | 18 | 93171 | LED18D38OW3840/25 | 120 | 6 | 5.31 | 1700 | 6500 | 4000K | 81 | 120 | 25,000 | Yes | ★ | Wet | 25° | White | |
| | E26 | 18 | 93311938 | LED18DP38ROW940/40 | 120 | 6 | 5.2 | 1700 | 4200 | 4000K | 90 | 150 | 25,000 | Yes | ★ | Wet | 40° | White | CEC Title 20 |
| | E26 | 18 | 93172 | LED18D38OW3840/40 | 120 | 6 | 5.31 | 1700 | 4400 | 4000K | 81 | 150 | 25,000 | Yes | ★ | Wet | 40° | White | |
| | E26 | 18 | 93311939 | LED18DP38ROW950/25 | 120 | 6 | 5.2 | 1700 | 6500 | 5000K | 90 | 120 | 25,000 | Yes | ★ | Wet | 25° | White | CEC Title 20 |
| | E26 | 18 | 93311940 | LED18DP38ROW950/40 | 120 | 6 | 5.2 | 1700 | 4200 | 5000K | 90 | 150 | 25,000 | Yes | ★ | Wet | 40° | White | CEC Title 20 |

¹ The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original lumen output (L70)

² Minimum order quantity = Carton Qty

★ ENERGY STAR³ status: ENERGY STAR³ certified. Lamps without a "★" are not ENERGY STAR³ certified.

³ UL 1993 Environmental Requirements for LED LAMPS

Damp Location - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to electrical equipment, including partially protected locations

Wet Location - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment

When installing outdoors, ensure the socket used is suitably Listed for use in Wet locations and socket gaskets provided by the manufacturer are correctly attached.




LED Lamps - Directional


LED PAR Lamps

CUSTOMER NAME _____
 PROJECT NAME _____
 DATE _____ NOTES _____


Directional Lamps (PAR38 - Value)

| Bulb Shape | Base Type | Watts | Order Code | Description | Volts | Carton Qty ² | MOL (in) | Lumens (Initial) | CBCP | Color Temp. (Initial) | CRI | Wattage Replacement | Rated Life L70 (Hrs) ¹ | Dimmable | ENERGY STAR [®] Status | Location Rating ³ | Beam Angle | Housing Color | Additional Information |
|--|-----------|-------|------------|------------------------|-------|-------------------------|----------|------------------|------|-----------------------|-----|---------------------|-----------------------------------|----------|---------------------------------|------------------------------|------------|---------------|------------------------|
| PAR38 - TIR Lens | | | | | | | | | | | | | | | | | | | |
|  | E26 | 15 | 93153880 | LED15DP38VOW830/35-4PK | 120 | 16 | 5.31 | 1300 | 2300 | 3000K | 80 | 90 | 15,000 | Yes | - | Wet | 35° | White | 4 pack |

Directional Lamps (PAR38 - High Output)

| Bulb Shape | Base Type | Watts | Order Code | Description | Volts | Carton Qty ² | MOL (in) | Lumens (Initial) | CBCP | Color Temp. (Initial) | CRI | Wattage Replacement | Rated Life L70 (Hrs) ¹ | Dimmable | ENERGY STAR [®] Status | Location Rating ³ | Beam Angle | Housing Color | Additional Information |
|--|-----------|-------|------------|------------------|---------|-------------------------|----------|------------------|-------|-----------------------|-----|---------------------|-----------------------------------|----------|---------------------------------|------------------------------|------------|---------------|------------------------|
| PAR 38 - High Output - TIR Lens | | | | | | | | | | | | | | | | | | | |
|  | E26 | 32 | 75447 | LED32DP38W830/15 | 120 | 6 | 5.12 | 3000 | 26000 | 3000K | 80 | 250 | 25,000 | Yes | ★ | Wet | 15° | White | |
| | E26 | 32 | 88801 | LED32DP38W830/25 | 120 | 6 | 5.12 | 3000 | 13000 | 3000K | 80 | 250 | 25,000 | Yes | ★ | Wet | 25° | White | |
| | E26 | 32 | 88810 | LED32DP38W830/40 | 120 | 6 | 5.12 | 3000 | 6000 | 3000K | 80 | 250 | 25,000 | Yes | ★ | Wet | 40° | White | |
| | E26 | 32 | 30233 | LED32DP38W835/15 | 120 | 6 | 5.12 | 3100 | 25000 | 3500K | 80 | 250 | 25,000 | Yes | ★ | Wet | 15° | White | |
| | E26 | 32 | 30237 | LED32DP38W835/25 | 120 | 6 | 5.12 | 3100 | 13000 | 3500K | 80 | 250 | 25,000 | Yes | ★ | Wet | 25° | White | |
| | E26 | 32 | 30239 | LED32DP38W835/40 | 120 | 6 | 5.12 | 3100 | 6000 | 3500K | 80 | 250 | 25,000 | Yes | ★ | Wet | 40° | White | |
| | E26 | 32 | 20109 | LED32P38W830/15 | 120-277 | 6 | 5.12 | 3000 | 25000 | 3000K | 80 | 250 | 25,000 | - | ★ | Wet | 15° | White | |
| | E26 | 32 | 20130 | LED32P38W830/25 | 120-277 | 6 | 5.12 | 3000 | 13000 | 3000K | 80 | 250 | 25,000 | - | ★ | Wet | 25° | White | |
| | E26 | 32 | 20137 | LED32P38W830/40 | 120-277 | 6 | 5.12 | 3000 | 6000 | 3000K | 80 | 250 | 25,000 | - | ★ | Wet | 40° | White | |

Directional Lamps (PAR38 - High Output)

| Bulb Shape | Base Type | Watts | Order Code | Description | Volts | Carton Qty ² | MOL (in) | Lumens (Initial) | CBCP | Color Temp. (Initial) | CRI | Wattage Replacement | Rated Life L70 (Hrs) ¹ | Dimmable | ENERGY STAR [®] Status | Location Rating ³ | Beam Angle | Housing Color | Additional Information |
|--|-----------|-------|------------|-------------------|-------|-------------------------|----------|------------------|-------|-----------------------|-----|---------------------|-----------------------------------|----------|---------------------------------|------------------------------|------------|---------------|------------------------|
| PAR 38 - High Output - TIR Lens | | | | | | | | | | | | | | | | | | | |
|  | E26 | 27 | 93314739 | LED27DP38OW830/15 | 120 | 6 | 5.3 | 3100 | 20000 | 3000K | 80 | 250 | 25,000 | Yes | - | Wet | 15° | White | |
| | E26 | 27 | 93314751 | LED27DP38OW830/25 | 120 | 6 | 5.3 | 3100 | 10000 | 3000K | 80 | 250 | 25,000 | Yes | - | Wet | 25° | White | |
| | E26 | 27 | 93314753 | LED27DP38OW830/40 | 120 | 6 | 5.3 | 3100 | 5000 | 3000K | 80 | 250 | 25,000 | Yes | - | Wet | 40° | White | |
| | E26 | 27 | 93314755 | LED27DP38OW835/15 | 120 | 6 | 5.3 | 3100 | 20000 | 3500K | 80 | 250 | 25,000 | Yes | - | Wet | 15° | White | |
| | E26 | 27 | 93314757 | LED27DP38OW835/25 | 120 | 6 | 5.3 | 3100 | 10000 | 3500K | 80 | 250 | 25,000 | Yes | - | Wet | 25° | White | |
| | E26 | 27 | 93314759 | LED27DP38OW835/40 | 120 | 6 | 5.3 | 3100 | 5000 | 3500K | 80 | 250 | 25,000 | Yes | - | Wet | 40° | White | |

¹ The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original lumen output (L70)

² Minimum order quantity = Carton Qty

★ ENERGY STAR[®] status: ENERGY STAR[®] certified. Lamps without a "★" are not ENERGY STAR[®] certified.

³ UL 1993 Environmental Requirements for LED LAMPS

Damp Location - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to electrical equipment, including partially protected locations

Wet Location - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment

When installing outdoors, ensure the socket used is suitably Listed for use in Wet locations and socket gaskets provided by the manufacturer are correctly attached.