



# LED Post Top Omnidirectional Corn Bulbs

8 to 120 Watts – 100-277VAC – 5500K White – E26 Edison or E39 Mogul Base



## FEATURES

- 5 Year LEDtronics Limited Warranty
- Direct Retrofit into E26 or E39 Base Fixtures
- Energy Savings of up to 85%
- Lumen Maintenance over 70% @ 40,000+ Hours
- Solid State – High Shock/Vibration Resistant
- Even, Omnidirectional Lighting
- Wide Oper. Temp. Range: -4°F to ~+149°F
- Safe to Use in Enclosed Luminaires
- UL/cUL Listed (E322319)
- RoHS Compliant – No Toxic Metals
- No UV/IR Radiation, No RF Transmission
- LED LM80 Report Available

## APPLICATIONS

- Street Lighting
- Outdoor Parking Areas Lighting
- Driveway & Walkway Lighting
- Security Lighting
- Parks / Playgrounds
- Rail Road Station Platforms
- Pendant Lighting
- Globe Lighting
- Garden Lighting
- Bollard Lighting

Over 30 Years of LEDtronics Design, Engineering & Manufacturing Experience



**LED19UL-08E26-XPW-101W** (8 Watts)  
**LED19UL-10E26-XPW-101W** (10 Watts)

|                          |                              |              |
|--------------------------|------------------------------|--------------|
| <b>Input Power</b>       | 9 Watts                      | 10 Watts     |
| <b>Input Voltage</b>     | 100~277VAC (Tested @ 120VAC) |              |
| <b>Input Current</b>     | 0.075A                       | 0.085A       |
| <b>Total Lumens</b>      | 1020 lm                      | 1180 lm      |
| <b>Max. Candela</b>      | 120 cd                       | 140 cd       |
| <b>Efficacy</b>          | 115                          |              |
| <b>Power Factor</b>      | 1.0                          |              |
| <b>LED Emitted Color</b> | Pure White                   |              |
| <b>Color Temperature</b> | 5700K~6300K                  |              |
| <b>CRI</b>               | >80                          |              |
| <b>Beam Angle</b>        | Omnidirectional              |              |
| <b>Heatsink</b>          | Aluminum                     |              |
| <b>Body</b>              | Polycarbonate / Gray & White |              |
| <b>Base</b>              | E26 Edison Screw             |              |
| <b>Oper. Temperature</b> | -4°F ~+149°F / -20°C ~+65°C  |              |
| <b>Weight</b>            | 0.51 lb/231g                 | 0.58 lb/263g |



## SUGGESTED APPLICATIONS

