



The bright white radiance of GE's LED A-Line lamps is not just something you see, it's something you feel.

# LED A-Line general purpose bulb

## PERFORMANCE DATA

### A-Line Lamps


Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty**	MOL (ln)	Lumens Initial	CBCP	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status	#Location Rating	Additional Information	
<b>A-15</b>																		
	MED	3	63011	LED3A15/W/TP	120	3	3.5	120		3000	80	-	15,000	-		Dry	White	
			63012	LED3A15/C/TP	120	3	3.5	120		3000	80	-	15,000	-		Dry	Clear	
			92122	LED3A15RED	120	3	3.5			Red				15,000	-		Damp	Red
			92125	LED3A15BLUE	120	3	3.5			Blue				15,000	-		Damp	Blue
			92126	LED3A15GREEN	120	3	3.5			Green				15,000	-		Damp	Green
			92132	LED3A15PINK	120	3	3.5			Pink				15,000	-		Damp	Pink
			23054	LED3A15ORNG	120	3	3.5			Orange				15,000	-		Damp	Orange
	MED	4.5	68173	LED4DA15-W/TP	120	3	3.5	270		2700	82	25W	15,000	Yes		Damp	White	
			68174	LED4DA15-C/TP	120	3	3.5	270		2700	82	25W	15,000	Yes		Damp	Clear	
			14644	LED4.5DA15-C/827	120	6	3.5	300		2700	80	40W	15,000	Yes		Damp	Clear	
			23708	LED4.5DA15-W5KTP	120	3	3.5	350		5000	80	40W	15,000	Yes		Damp	White	
			23724	LED4.5DA15-C5KTP	120	3	3.5	350		5000	80	40W	15,000	Yes		Damp	Clear	
			83645	LED4.5DA15C-FRIG	120	3	3.5	350		5000	80	40W	15,000	Yes		Damp	Clear Refrigerator bulb	
<b>A-19</b>																		
	MED	7	14063	LED7DAV3/827W	120	6	4.6	470		2700	80	40W	25,000	Yes		Damp	White, Semi-Omni	
			95928	LED7DAV3/5K	120	6	4.6	500		5000	80	40W	25,000	Yes		Damp	White, Semi-Omni	
			11332	LED7DA19/827	120	6	4.4	450		2700	80	40W	25,000	Yes	★	Damp	White, Omnidirectional	
			71208	LED7DA19/830	120	6	4.4	450		3000	80	40W	25,000	Yes	★	Damp	White, Omnidirectional	
			34238	LED7DA19/824	120	6	4.44	450		2400	80	40W	25000	Yes		Damp	White	
			10.5	13791	LED11DAV3/827W	120	6	4.6	800		2700	80	60W	15,000	Yes		Damp	White, Semi-Omni
				95927	LED11DAV3/5K	120	6	4.4	850		5000	80	60W	15,000	Yes		Damp	White, Semi-Omni
			11	11328	LED11DA19/827	120	6	4.4	800		2700	80	60W	25,000	Yes	★	Damp	White, Omnidirectional
				71209	LED11DA19/830	120	6	4.4	800		3000	80	60W	25,000	Yes	★	Damp	White, Omnidirectional
				29268	LED11DA19/824	120	6	4.44	800		2400	80	60W	25,000	-		Damp	White
74357	LED11DA19827GU24	120	6	5.43	800		2700	80	60W	25,000	-	★	Damp	White				
<b>A-Line reveal®</b>																		
	MED	7	63178	LED7DA19RVLESTP	120	3	4.43	450		2700	84	40w	25,000	Yes		Damp	White, Omnidirectional	
			11	63180	LED11DA19RVLESTP	120	3	4.43	800		2700	84	60w	25,000	Yes		Damp	White, Omnidirectional
<b>A-21</b>																		
	MED	12	73384	LED12A21/830FE	120	6	5.31	1100		3000	80	100W	25,000	Yes		Damp	Enclosed	
			73404	LED12DA21/850FE	120	6	5.31	1100		5000	80	100W	25,000	Yes		Damp	Enclosed	
			13	14075	LED13DA21/827	120	6	5.3	1100		2700	80	75W	25,000	Yes	★	Damp	White, Omnidirectional
			14	94936	LED14DA21/827W	120	6	5.3	1100		2700	80	75W	15,000	Yes		Damp	White, Semi-Omni
			16	14074	LED16DA21/827	120	6	5.3	1600		2700	80	100W	25,000	Yes	★	Damp	White, Omnidirectional
	GU24	MED	92498	LED16DA21827GU24	120	6	5.43	1600		2700	80	100W	25,000	Yes	★	Damp	White	
			73376	LED16A30/100/827	120	6	5.31	400/1600/1050		2700	80	30/70/100	25,000	-		Damp	3-Way	
			92118	LED16A30/100/5KB	120	3	5.31	400/1600/1050		5000	80	30/70/100	25,000	-			White, 3-Way	
			34236	LED16DA21/830	120	6	5.3	1600		3000	80	100W	25,000	Yes	★	Damp	White, Omnidirectional	
			17	16113	LED17DA21/827	120	6	5.3	1600		2700	78	100W	15,000	Yes		Damp	White, Semi-Omni
			22	73378	LED22A50/150/827	150	6	5.31	700/2155/1600		2700	80	50/100/150	25,000	-		Damp	3-Way
			92120	LED22A50/150/5KB	120	3	5.31	700/2155/1600		5000	80	50/100/150	25,000	-			White, 3-Way	

For additional product and application information, please consult GE's website: [gelighting.com/ThinkLED](http://gelighting.com/ThinkLED)


Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

\* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)  
 \*\* Minimum order quantity = 6  
 ★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a ★ are not ENERGY STAR® certified.  
 # UL 1993 Environmental Requirements for LED LAMPS  
 Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.  
 Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.  
 Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.  
 Notes: 1) Product descriptions ending in "/TP" indicate a corded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.  
 2) LED A19 Locking device works on PC: 85791, 85792, 89898, 62182, 89899 and 89900

## CHROMATICITY DIAGRAM



## SPECTRAL POWER DISTRIBUTION



For additional product and application information, visit [www.gelighting.com/ThinkLED](http://www.gelighting.com/ThinkLED)



Product is compliant with material restriction requirements of RoHS

ENERGY STAR® is a registered U.S. mark



[www.gelighting.com](http://www.gelighting.com)

GE and the GE Monogram are trademarks of the General Electric Company. All other trademarks are the property of their respective owners. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions. GE Lighting and GE Lighting Solutions, LLC are businesses of the General Electric Company. © 2015 GE.

69170 (Rev 8/3/15)