

enhance



The versatile radiance of GE's dimmable candle lamps is not just something you see, it's something you feel.

LED dimmable candle lamps

For any decorative lighting application, GE's LED dimmable candle lamps are the perfect solution and offer a multitude of wattage options.

LOW-COST OPERATION

- For example, using only 2.2 watts of energy, save over \$21 in energy costs over the rated life of a lamp versus a standard 15-watt incandescent lamp based on \$0.11 per kWh
- Energy efficiency and long life mean fewer lamp replacements versus standard incandescent and halogen light sources

EXCELLENT COLOR RENDERING

- Available with a CRI of 80 - 82
- Candles have "sparkle" similar to incandescent

COLOR TEMPERATURE

- Halogen-like color
- Available in 2400K, 2700K and 5000K

LONG LIFE

- Up to 15,000 hours rated life (L70)

DIMMABLE

- Dims from 100% to 10%

ENVIRONMENTALLY CONSCIOUS

- These lamps are energy efficient, contain no lead or mercury, and are compliant with material restriction requirements of RoHS

GE QUALITY AND RELIABILITY

- 3-year limited warranty

To learn more about saving money and energy, go to: gelighting.com/ThinkLED

When you Think LED lighting, Think GE.

ecomaginationSM



imagination at work

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

LED dimmable candle lamps

Decorative Lamps

Bulb Shape	Base Type	Watts	Order Code	Description	Volts	Case Qty	MOL (in)	Lumens Initial	CBCP	Initial Color Temp	CRI	Wattage Replacement	*Rated Life L70 (Hrs)	Dimmable	ENERGY STAR® Status	#Location Rating	Additional Information		
Candles																			
	CA11	MED	3.5	68168	LED3DCAM-C/TP	120	3	4.2	170	2700	80	25W	15,000	Yes		Damp	Clear, Bent tip		
			4	68167	LED4DCAM-F/TP	120	3	4.2	270	2700	82	25W	15,000	Yes		Damp	Frost, Bent tip		
				21250	LED4DCAM-C3/827	120	6	4.2	300	2700	80	40W	15,000	Yes	★	Damp	Clear, Bent tip		
				69111	LED4DCAM-C3/850	120	6	4.2	300	5000	80	40W	15,000	Yes	★	Damp	Clear, Bent tip		
				75554	LED4DCAMCF/824	120	6	4.2	250	2400	80	25W	15,000	Yes		Damp	Clear, Bent tip		
	CAND	3.5		21251	LED7DCAM-C3/827	120	6	4.8	500	2700	80	60W	15,000	Yes	★	Damp	Clear, Bent tip		
				68166	LED3DCAC-C/TP	120	3	4.3	170	2700	80	25W	15,000	Yes		Damp	Clear, Bent tip		
				4	68165	LED4DCAC-F/TP	120	3	4.3	270	2700	82	25W	15,000	Yes		Damp	Frost, Bent tip	
				21231	LED4DCAC-C3/827	120	6	4.3	300	2700	80	40W	15,000	Yes	★	Damp	Clear, Bent tip		
				69109	LED4DCAC-C3/850	120	6	4.3	300	2700	80	40W	15,000	Yes	★	Damp	Clear, Bent tip		
				75553	LED4DCACCF/824	120	6	4.3	250	2400	80	25W	15,000	Yes		Damp	Clear, Bent tip		
				7	21233	LED7DCAC-C3/827	120	6	4.8	500	2700	80	60W	15,000	Yes	★	Damp	Clear, Bent tip	
			Globes																
	G16.5	CAND	4.5	68169	LED4DG16C-W/TP	120	3	3.0	270	2700	82	25W	15,000	Yes		Damp	White		
				68170	LED4DG16C-C/TP	120	3	3.0	270	2700	82	25W	15,000	Yes		Damp	Clear		
	G25	MED	4.5		68171	LED4DG25M-W/TP	120	3	4.3	280	2700	82	25W	15,000	Yes		Damp	White	
					68172	LED4DG25M-C/TP	120	3	4.3	280	2700	82	25W	15,000	Yes		Damp	Clear	
					21253	LED5DG25-W3/827	120	6	4.3	350	2700	80	40W	15,000	Yes	★	Damp	White	
					7	21255	LED7DG25-W3/827	120	6	4.3	500	2700	80	60W	15,000	Yes	★	Damp	White

Get more information at
GELighting.com/ThinkLED

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

** Minimum order quantity = 6

★ ENERGY STAR® status: ENERGY STAR® certified. Lamps without a ★ are not ENERGY STAR® certified.

UL 1993 Environmental Requirements for LED LAMPS

Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.

Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.



Product is compliant with material restriction requirements of RoHS

ENERGY STAR® is a registered U.S. mark



www.gelighting.com

GE and the GE Monogram are trademarks of the General Electric Company. All other trademarks are the property of their respective owners. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions. GE Lighting and GE Lighting Solutions, LLC are businesses of the General Electric Company. © 2016 GE.

65028 (Rev 12/05/16)