PRODUCT DATASHEET
LED A19 5.5W DIM FR 2700K 1PK

SYLVANIA ULTRA A19 Lamps | Dimmable ULTRA A19 LED lamps with 80+ CRI and 15,000-hour rated life



Areas of application

- Downlights, pendant fixtures, table lamps, wall sconces
- Healthcare, hospitality, residential, retail
- Indoor and outdoor
- Suitable for rough service

Product features

- 15,000 hours lifetime (L70)
- RoHS compliant, mercury and lead free
- UV and IR free
- Reduces energy consumption up to 85 %
- Last up to 20 times longer than incandescent lamps
- No warm-up time, instant-on with full light output and stable color
- Dimmable down to 10 %
- Approved for enclosed fixtures



© 2026, LEDVANCE GmbH. All rights reserved.

TECHNICAL DATA

Additional product data

Base type	E26
Mercury content	0.0 mg
Mercury-free	Yes
Ordering Abbreviation	LED5.5A19DIMO827URP
Abbrev. With Packaging Info.	LED5.5A19DIMO827URP 6/CS 1/SKU
SKU UPC	0046135746888
NAED	74688
Family Brand Name	ULTRA
General Description	LED A19, 5.5W, Dimmable, 80CRI, 450 Lumen, 2700K, 15000 Life, E26 Medium Base, FROSTED Finish

Electrical data

Nominal Wattage	5.50 W
Nominal voltage	120.00 V
Claimed Equivalent Lamp Pwr	40 W
Supply Frequency	50…60 Hz

Photometrical data

Lumens	450 lm
Efficacy	82
Color Temperature/CCT	2700 K
Color Rendering Index (CRI)	80
Light color	827

Dimensions & Weight

Overall length	107.01 mm
Diameter	2.36 in
Product weight	0.13 lb

Materials & Colors

Lamp Finish	Frosted
Bulb shape	A19
Bulb Glass Type	PLASTICS

© 2026, LEDVANCE GmbH. All rights reserved.

Application & Mounting

Dimming	Yes

Temperatures & operating conditions

Ambient temperature range	-20…+45 °C

Lifespan

Average Rated Life (hr)	15000

Capabilities

Dimming	Yes

Certificates & Standards

Certification Listing	RoHS / CSA / FTC / FCC / cULus
Energy Star Rated	X

Logistical data

SKU Qty	1
Case Qty	6
Case Length (in)	8.110
Case Width (in)	5.787
Case Depth (in)	4.882
Case Cube (ft)	0.133
Case Weight (lbs)	1.455
SKU UPC	0046135746888
Pallet Qty	2,268

Safety advice

- Suitable for damp locations.
- Not for use with emergency light fixtures or exit lights.
- -4°F and + 113°F (-20°C and +45°C)

DOWNLOAD DATA

	Spec Sheets and Product Documents	Document name
PDF	Product Family Spec Sheet	ULTRA LED A-line Lamps

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2026, LEDVANCE GmbH. All rights reserved.