

Flanged Based

- T-1 3/4 (5mm)
- 100,000 Life Hours
- Ultra-Bright Output
- Single Chip Diode

[Cross Reference Guide](#)



Part Number (#):	Voltage (V):	Current (mA):	Wattage (W):	Dimensions:	Emitted Color:	Output (mcd):	Viewing Angle:	Replaces:
LED6MFWW-DC	6V	80	0.50	15.3mm L x 5mm D	White □	500	120°	Flanged Based Bulb
LED6MFR-DC	6V	80	0.50	15.3mm L x 5mm D	Red ■	500	120°	Flanged Based Bulb
LED6MFG-DC	6V	80	0.50	15.3mm L x 5mm D	Green ■	500	120°	Flanged Based Bulb
LED6MFY-DC	6V	80	0.50	15.3mm L x 5mm D	Yellow ■	500	120°	Flanged Based Bulb
LED6MFA-DC	6V	80	0.50	15.3mm L x 5mm D	Amber ■	500	120°	Flanged Based Bulb
LED6MFB-DC	6V	80	0.50	15.3mm L x 5mm D	Blue ■	500	120°	Flanged Based Bulb

Voltage: 6VDC Current: 80mA, Wattage: 0.50W, Type: T1-3/4 (5MM) LED, Light Output: 500 mcd, Base Type:- MF (midget flange base), Life Hours: 100,000, Dimensions: 15.3mm Length x 5mm Diameter, Viewing Angle: 120 Degree