



Product Number: 65528

Order Abbreviation: LEDRT56675850BA

General Description: LED RT 5/6' 675lm, 5000K, 35,000h, Baffle Reflector type.

Product Information

Diameter (in)	7.32 in
Diameter (mm)	185.93 mm
Power Factor	?0.90
Primary Lamp Type	SMD
Minimum Operating Temperature - Celsius	-20
Minimum Operating Temp - Fahrenheit	-4
Primary Lamp Type 1	SMD
Total Harmonic Distortion (THD)	< 20 %
Efficacy (LPW)	74 lm/W
Operating Temperature (°C)	-20?+40 °C
Operating Voltage (V)	120
Abbrev. With Packaging Info.	LEDRT56675850BA 4/CS 2/SKU
Base	E26 Medium
Ordering Abbreviation	LEDRT56675850BA
Average Rated Life 1 (hr)	35000
Nominal Wattage (W)	8.50
UPC Code	046135655289
Color Rendering Index (CRI)	80
Service Life Rating	35000
Lumens (lm)	675
Color Temperature/CCT (K)	5000
Fixture Warranty	5 years
Housing	Plastic
Luminaire Finish	White
Luminaire Type	Downlight
Maximum Operating Temperature-Celsius	40
Maximum Operating Temperature-Fahrenheit	104
Mounting	Recessed
Dimensions	2.56
Certification Listing	RoHS,FCC
Number of Lamps	1
Open Circuit Voltage (V)	1
Height (in)	2.56 in
Height (mm)	65.02 mm
Width (in)	7.32 in

Width (mm)	185.93 mm
Product Weight (g)	220.00