

LumenChoice™ Type C LED Tube and Driver System

Lamp Performance-Regular Drivers



2'-4' T5 HO and Regular Driver										
4ft Glass				Driver		LED18T8/DR/XX	LED21T8/DR/XX	LED36T8/DR/XX	Notes	
Lamp Product Code	Lamp Description	CCT	DLC [®]	Wattage		18W	21W	36W		
38926	LEDT5/LC/G/4/830	3000K	-	Initial Lumens		2100	2500	4300	Available Q3 2019	
38934	LEDT5/LC/G/4/835	3500K	-			2150	2500	4350	Available Q3 2019	
38940	LEDT5/LC/G/4/840	4000K	-			2200	2550	4400	Available Q3 2019	
38946	LEDT5/LC/G/4/850	5000K	-			2200	2550	4400	Available Q3 2019	
3ft Glass				Driver		LED15T8/DR/XX	LED18T8/DR/XX	LED21T8/DR/XX	Notes	
Lamp Product Code	Lamp Description	CCT	DLC [®]	Wattage		15W	18W	21W		
38947	LEDT5/LC/G/3/830	3000K	-	Initial Lumens		1750	2100	2500	Available Q3 2019	
38948	LEDT5/LC/G/3/835	3500K	-			1800	2150	2550	Available Q3 2019	
38949	LEDT5/LC/G/3/840	4000K	-			1850	2200	2600	Available Q3 2019	
38955	LEDT5/LC/G/3/850	5000K	-			1850	2200	2600	Available Q3 2019	
2ft Glass				Driver		LED9T8/DR/XX	LED12T8/DR/XX	LED15T8/DR/XX	LED18T8/DR/XX	Notes
Lamp Product Code	Lamp Description	CCT	DLC [®]	Wattage		9W	12W	15W	18W	
38968	LEDT5/LC/G/2/830	3000K	-	Initial Lumens		1050	1400	1800	2150	Available Q3 2019
38980	LEDT5/LC/G/2/835	3500K	-			1100	1450	1850	2200	Available Q3 2019
38983	LEDT5/LC/G/2/840	4000K	-			1150	1500	1900	2250	Available Q3 2019
38992	LEDT5/LC/G/2/850	5000K	-			1150	1500	1900	2250	Available Q3 2019
2'-4' T5 HE and Regular Driver										
4ft Glass				Driver		LED12T8/DR/XX	LED15T8/DR/XX	LED18T8/DR/XX	LED21T8/DR/XX	Notes
Lamp Product Code	Lamp Description	CCT	DLC [®]	Wattage		12W	15W	18W	21W	
38993	LEDT5LC/G4/830HE	3000K	-	Initial Lumens		1500	1900	2250	2650	Available Q3 2019
38995	LEDT5LC/G4/835HE	3500K	-			1500	1950	2300	2700	Available Q3 2019
38998	LEDT5LC/G4/840HE	4000K	-			1550	2000	2350	2750	Available Q3 2019
38999	LEDT5LC/G4/850HE	5000K	-			1550	2000	2350	2750	Available Q3 2019
3ft Glass				Driver		LED9T8/DR/XX	LED12T8/DR/XX	LED15T8/DR/XX	Notes	
Lamp Product Code	Lamp Description	CCT	DLC [®]	Wattage		9W	12W	15W		
39000	LEDT5LC/G3/830HE	3000K	-	Initial Lumens		1100	1500	1850	Available Q3 2019	
39001	LEDT5LC/G3/835HE	3500K	-			1150	1550	1900	Available Q3 2019	
39002	LEDT5LC/G3/840HE	4000K	-			1150	1600	1950	Available Q3 2019	
39003	LEDT5LC/G3/850HE	5000K	-			1150	1600	1950	Available Q3 2019	
2ft Glass				Driver		LED9T8/DR/XX	LED12T8/DR/XX	LED15T8/DR/XX	Notes	
Lamp Product Code	Lamp Description	CCT	DLC [®]	Wattage		9W	12W	15W		
39004	LEDT5LC/G2/830HE	3000K	-	Initial Lumens		1100	1450	1800	Available Q3 2019	
39005	LEDT5LC/G2/835HE	3500K	-			1150	1500	1850	Available Q3 2019	
39006	LEDT5LC/G2/840HE	4000K	-			1200	1550	1900	Available Q3 2019	
39016	LEDT5LC/G2/850HE	5000K	-			1200	1550	1900	Available Q3 2019	

Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)
 # UL 1993 Environmental Requirements for LED LAMPS
 Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.
 Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.
 Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

LumenChoice™ Type C LED Tube and Driver System

Lamp Performance-LumenChoice™ Drivers (Limited Availability - Rolling Transition)



2'-4' T5 HO and LumenChoice Driver										
4ft Glass				Driver	High Watt LumenChoice Driver			21383 - LED/DR/D2L/HW 21392 - LED/DR/D4L/HW		
Lamp Product Code	Lamp Description	CCT	DLC ^o	Wattage	18W	19.5W	21W	23W	25W	Notes
38926	LEDT5/LC/G/4/830	3000K	-	Initial Lumens	2100	2250	2500	2700	2950	Available Q3 2019
38934	LEDT5/LC/G/4/835	3500K	-		2150	2300	2500	2750	3000	Available Q3 2019
38940	LEDT5/LC/G/4/840	4000K	-		2200	2350	2550	2800	3050	Available Q3 2019
38946	LEDT5/LC/G/4/850	5000K	-		2200	2350	2550	2800	3050	Available Q3 2019
3ft Glass				Driver	High Watt LumenChoice Driver			21383 - LED/DR/D2L/HW 21392 - LED/DR/D4L/HW		
Lamp Product Code	Lamp Description	CCT	DLC ^o	Wattage	18W	19.5W	21W	23W	25W	Notes
38947	LEDT5/LC/G/3/830	3000K	-	Initial Lumens	2100	2300	2500	2700	2950	Available Q3 2019
38948	LEDT5/LC/G/3/835	3500K	-		2150	2350	2550	2750	3000	Available Q3 2019
38949	LEDT5/LC/G/3/840	4000K	-		2200	2400	2600	2800	3050	Available Q3 2019
38955	LEDT5/LC/G/3/850	5000K	-		2200	2400	2600	2800	3050	Available Q3 2019
2ft Glass				Driver	Low Watt LumenChoice Driver			21378 - LED/DR/D2L/LW 21379 - LED/DR/D4L/LW		
Lamp Product Code	Lamp Description	CCT	DLC ^o	Wattage	8W	9W	12W	15W	16.5W	Notes
38968	LEDT5/LC/G/2/830	3000K	-	Initial Lumens	950	1050	1400	1800	1950	Available Q3 2019
38980	LEDT5/LC/G/2/835	3500K	-		950	1100	1450	1850	2000	Available Q3 2019
38983	LEDT5/LC/G/2/840	4000K	-		1000	1150	1500	1900	2050	Available Q3 2019
38992	LEDT5/LC/G/2/850	5000K	-		1000	1150	1500	1900	2050	Available Q3 2019
2'-4' T5 HE and LumenChoice Driver										
4ft Glass				Driver	High Watt LumenChoice Driver			21383 - LED/DR/D2L/HW 21392 - LED/DR/D4L/HW		
Lamp Product Code	Lamp Description	CCT	DLC ^o	Wattage	18W	19.5W	21W	23W	25W	Notes
38993	LEDT5LC/G4/830HE	3000K	-	Initial Lumens	2250	2450	2650	2900	3150	Available Q3 2019
38995	LEDT5LC/G4/835HE	3500K	-		2300	2500	2700	2950	3200	Available Q3 2019
38998	LEDT5LC/G4/840HE	4000K	-		2350	2550	2750	3000	3250	Available Q3 2019
38999	LEDT5LC/G4/850HE	5000K	-		2350	2550	2750	3000	3250	Available Q3 2019
4ft Glass				Driver	Low Watt LumenChoice Driver			21378 - LED/DR/D2L/LW 21379 - LED/DR/D4L/LW		
Lamp Product Code	Lamp Description	CCT	DLC ^o	Wattage	8W	9W	12W	15W	16.5W	Notes
38993	LEDT5LC/G4/830HE	3000K	-	Initial Lumens	1000	1100	1500	1900	2050	Available Q3 2019
38995	LEDT5LC/G4/835HE	3500K	-		1000	1150	1500	1950	2100	Available Q3 2019
38998	LEDT5LC/G4/840HE	4000K	-		1050	1200	1550	2000	2150	Available Q3 2019
38999	LEDT5LC/G4/850HE	5000K	-		1050	1200	1550	2000	2150	Available Q3 2019
3ft Glass				Driver	High Watt LumenChoice Driver			21378 - LED/DR/D2L/LW 21379 - LED/DR/D4L/LW		
Lamp Product Code	Lamp Description	CCT	DLC ^o	Wattage	8W	9W	12W	15W	16.5W	Notes
39000	LEDT5LC/G3/830HE	3000K	-	Initial Lumens	950	1100	1500	1850	2050	Available Q3 2019
39001	LEDT5LC/G3/835HE	3500K	-		1000	1150	1550	1900	2100	Available Q3 2019
39002	LEDT5LC/G3/840HE	4000K	-		1050	1150	1600	1950	2150	Available Q3 2019
39003	LEDT5LC/G3/850HE	5000K	-		1050	1150	1600	1950	2150	Available Q3 2019
2ft Glass				Driver	Low Watt LumenChoice Driver			21378 - LED/DR/D2L/LW 21379 - LED/DR/D4L/LW		
Lamp Product Code	Lamp Description	CCT	DLC ^o	Wattage	8W	9W	12W	15W	16.5W	Notes
39004	LEDT5LC/G2/830HE	3000K	-	Initial Lumens	950	1100	1450	1800	2000	Available Q3 2019
39005	LEDT5LC/G2/835HE	3500K	-		1000	1150	1500	1850	2050	Available Q3 2019
39006	LEDT5LC/G2/840HE	4000K	-		1050	1200	1550	1900	2100	Available Q3 2019
39016	LEDT5LC/G2/850HE	5000K	-		1050	1200	1550	1900	2100	Available Q3 2019

Updated / New Product

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)
 # UL 1993 Environmental Requirements for LED LAMPS
 Location, damp - Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.
 Location, dry - Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.
 Location, wet - Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.