



LED Twin Tube 2G11

LINEAR FLUORESCENT RETROFIT LAMP

For: Fluorescent replacement

FEATURES AND BENEFITS

- Efficacy of 130LPW
- Type-B (Direct-Wire)- Removal of ballast required for normal operation
- Single-ended power; INPUT end is electrically connected, other end has no electrical connection
- Flicker-free LED lighting



PRODUCT SPECIFICATIONS

Length	16" and 21" versions
Body	Oval extruded aluminum/ polycarbonate lens
Lens	Frosted
Connection	2G11 end cap
Input Voltage	100-277VAC, 50/60hz
Driver	Single end power; integrated LED driver
Available colors	Warm white 3500K Neutral white 4000K Cool white 5000K
CRI	>80
Dimming	Non-dimmable
Lifetime	L70 ≥ 60,000 hours
Warranty	10-year warranty
Environmental Requirements	Operating temp: -20° to 50°C Storage temp: -30° to 60°C Working humidity: 30% to 85% Storage humidity: 10% to 90% Non-corrosive environments
Power Factor	>0.9
Beam Angle	120°

32000 Aurora Road, Suite B, Solon, OH 44139 • energyfocus.com • 800.327.7877

©2018 Energy Focus, Inc. All Rights Reserved. Energy Focus, Inc. reserves the right to change specifications for product improvement without prior notice.



PRODUCT SPECIFICATION

PART NUMBER	SIZE NOMINAL	POWER	LUMINOUS FLUX	UL PART NUMBER
LEDTT-835-1609	16"	8.5W	1105lm	Same as part number
LEDTT-840-1609	16"	8.5W	1105lm	Same as part number
LEDTT-850-1609	16"	8.5W	1105lm	Same as part number
LEDTT-835-2114	21"	14W	1820lm	Same as part number
LEDTT-840-2114	21"	14W	1820lm	Same as part number
LEDTT-850-2114	21"	14W	1820lm	Same as part number

LINE DIAGRAM

