

TESTING AND CODE COMPLIANCE

- UL Listed (File #E-3810)
- CSA Certified (File #LR-1863)
- NOM Certified (File #057), except interiors

Multi-Lampholder Clusters

Specifications and Features

- Pull chain models have bell at end of chain on 3 foot cord
- Medium and Candelabra bases
- Par connectors have white, unglazed porcelain body

MEDIUM BASE MULTI-LAMPHOLDER CLUSTERS

Treated Aluminum Screw Shell

Description	Rating	Cat. No.	T	TA	B	BA	OAH T+B
2-Light Twin 1/8 IPS Male Top Bracket Only	660W 250V	4020-A3A	1 ⁵ / ₁₆	5/16	—	—	—
2-Light Twin 1/8 IPS Male (top & bottom)	660W 250V	4015-D4F	1 ¹¹ / ₁₆	5/16	1 ¹¹ / ₁₆	7/16	3 ³ / ₈
2-Light Offset 1/8 IPS Male (top & bottom)	660W 250V	4032-E5F	1 ³ / ₄	5/16	1 ³ / ₄	7/16	3 ¹¹ / ₁₆
3-Light 1/8 IPS Male (top & bottom)†	660W 250V	341-D4U	1 ³ / ₄	1/2	1 ³ / ₄	7/16	3 ¹ / ₂
2-Light Offset 1/8 IPS Male (top); Pullchain Switch (bottom) with 1/2" usable shank◊	660W 250V 1A 125V T	4034-F5A	1 ³ / ₄	5/16	1 ¹⁵ / ₁₆	1/2	3 ³ / ₄ +
2-Light Twin 1/8 IPS Male (top); Pullchain Switch (bottom) 3/8" usable shank◊	660W 250V 1A 125V T	4017-D2F	1 ¹ / ₁₆	5/16	1 ¹¹ / ₁₆	3/8	2 ¹³ / ₁₆ +

†Includes nut. Leads are No. 18 AWG 105°C plastic; 9" long, stripped 3/4"; untinned and pulled through top bracket.

All devices are UL Listed except Cat. No. 905. Also CSA Certified except where indicated by ◊, and NOM Certified except where indicated by †.

PORCELAIN PAR CONNECTORS

Description	Rating	Cat. No.
Medium Base for PAR #46 and #38 lamps. Leads are No. 14 AWG 200°C SEW-2 Silicone Rubber Insulated; 18" Long, Stripped 3/4". Others available on inquiry†	660W 125V	368-1
Mogul Base for PAR #56 and #64 lamps. Leads are No. 14 150°C SEWF-2; 18" Long, Stripped 3/4". Others available upon request	1000W 125V	357-8

All devices are UL Listed except Cat. No. 905. Also CSA Certified except where indicated by ◊, and NOM Certified except where indicated by †.

BAYONET SOCKET — SINGLE CONTACT

Candelabra Base

Description	Rating	Cat. No.
Flat Bracket. Leads are No. 18 AWG, 105°C Plastic; 6" Long, Stripped 3/4" (one black, one white)◊†	Low Voltage	905



4034-F5A



341-D4U



4032-E5F