

NEMA Locking Devices

LIFETIME WARRANTY

BLACK & WHITE
INDUSTRIAL GRADE PLUGS & CONNECTORS



2730



2731



2733



2735



2736

15/20/30 Amp NEMA Locking Devices

POLES/WIRES	AMPS	VOLTS	NEMA	AC HP RATING	RECEPTACLE	PLUG	CONNECTOR	FLANGED INLET	FLANGED OUTLET	
Locking 2-Pole 3-Wire Grounding	15	125V	L5-15	.5	4710	4720-C	4729-C	4716-C	4715-C	
		250V	L6-15	1.5*	4560	4570-C	4579-C	4586-C	4585-C	
		277V AC	L7-15	2	4760	4770-C	4779-C	4786-C	4785-C	
	20	125V	L5-20	1	2310	2311	2313	2315	2316	
		250V	L6-20	2*	2320	2321	2323	2325	2326	
		277V AC	L7-20	2	2330	2331	2333	2335	2336	
		347V AC	L24-20	N/A	3720	3721	3723	3755	3756	
		480V AC	L8-20	3	2340	2341	2343	2345	2346	
		600V AC	L9-20	N/A	2350	2351	2353	2355	2356	
30	125V	L5-30	2	2610	2611	2613	2615	2616		
	250V	L6-30	2*	2620	2621	C2623	2625F	2626F		
	277V AC	L7-30	3	2630	2631	2633	2635	2636		
	480V AC	L8-30	5	2640	2641	2643	2645	2646		
	600V AC	L9-30	N/A	2650-A	C2651	C2653	2655	2656		
Locking 3-Pole 3-Wire Grounding	15	3ø 250V	L11-15	2	4870	4880-C	4889	-	-	
		20	125/250V	L10-20	2L-L*/1 L-N	2360	2361	2363	2365	2366
	3ø 250V		L11-20	2L-L*/2 L-N	2370	2371	2373	2375	2376	
	3ø 480V		L12-20	5	2380	2381	2383	2385	2386	
	30		125/250V	L10-30	2L-N	2660-A	2661	2663	2665	2666
		3ø 250V	L11-30	3	2670	2671	2673	2675	2676	
Locking 3-Pole 4-Wire Grounding	20	3ø 480V	L12-30	10	2680	2681	2683	2685	2686	
		3ø 600V	L13-30	N/A	2690	2691	2693	2695	2696	
		30	125/250V	L14-20	2L-L*/1 L-N	2410	2411	2413	2415	2416
	3ø 250V		L15-20	3	2420	2421	2423	2425	2426	
	3ø 480V		L16-20	3	2430	2431	2433	2435	2436	
	Locking 4-Pole 4-Wire Grounding	20	3øY 120/208V	L18-20	2	2440	2441	2443	2445	2446
3øY 277/480V			L19-20	5	2450	2451	2453	2455	2456	
3øY 347/600V			L20-20	N/A	2460	2461	2463	2465	2466	
30		3øY 120/208V	L18-30	3	2750	2751	2753	2755	2756	
		3øY 277/480V	L19-30	10	2760	2761	2763	2765	2766	
Locking 4-Pole 5-Wire Grounding	20	3øY 347/600V	L20-30	N/A	2770	2771	2773	2775	2776	
		30	3øY 120/208V	L21-20	2	2510	2511	2513	2515	2516
			3øY 277/480V	L22-20	5	2520	2521	2523	2525	2526
	3øY 347/600V		L23-20	N/A	2530	2531	2533	2535	2536	
	30	3øY 120/208V	L21-30	3	2810	2811	2813	2815	2816	
		3øY 277/480V	L22-30	10	2820	2821	2823	2825	2826	
3øY 347/600V		L23-30	N/A	2830	2831	2833	2835	2836		

* Suitable for 208V motor applications at HP rating L-L Denotes phase-to-phase HP rating L-N Denotes phase-to-neutral HP rating