



Sunlite 2X4 Rectangle LED Lay-In Troffer Fixture, 3000K - Warm White, White Finish

Sunlite's LED flat panels are usually used to replace 2X2, 1X4 and 2X4 fluorescent fixtures. It's slim design is a easy installation to lay in drop ceilings.



General Characteristics

Fixture Life Hours	25000 Hours
Material	Aluminum
Lens	Flat Panel
Lens Finish	White
Bulb	Integrated LED
Finish	White
Lumens Per Watt (LPW)	100.00
Life (based on 3hr/day)	22.8
Estimated Energy Cost	\$7.23 per Year
Safety Rating	ETL - Damp Location
Dimmable	True
DLC	True

Fixture Characteristics

Shape	Rectangle
Number of Lights	1 - Light
Mounting	Recessed
Use Location	Indoor

Electrical Characteristics

Watts	60
Volts	100-277
LED Chip Manufacturer	SMD2835
Number of LEDs	288
Power Factor	0.9
Operating Temperature	-20° to 45°

Light Characteristics

Brightness	6000 Lumens
Color Accuracy (CRI)	80
Light Appearance	Warm White
Color Temperature	3000K
Beam Angle	100°

Product Dimensions

Size	2X4
Height (in)	23.74
Diameter (in)	47.75
Item Dimensions (in)	(W) 23.80 (H) 0.37 (D) 47.80

Product Data

Item Number	85380-SU
Case Quantity	4
Barcode on SKU	653703853802
Brand	SUNLITE
Description	LFX/2X4/60W/DLC/30K/D/MV/0-10V/2PK
DLC File Number	PL2DSMRCWCKR