

LED Commercial Recessed Wattage / Color Selectable Downlights

- Instant start integrated LED chips
- Wattage and white color selectable
- 90 CRI for true color appearance
- 120-347 multi-volts
- 0-10V Dimming
- 90° beam angle
- Type-IC for direct contact with insulation
- NEC rated BX cable connection
- Attached safety cable
- Clamp system for canless installation
- Rated for damp locations
- 50,000 lifetime hours
- Available 4", 6", 8", and 9.5"



Item#	Description	Watt	Lumen	CRI	Volt	Color Temp	Hours	Features	Dimension(in)
87808-SU	LFX/CRD/4R/90CRI/3MW/5SCT/V2	9/13/18	1000/1500/2000	90	120-347	27K/30K/35K/40K/50K	50000	DL,DIM,ES	4.0(h) 5.9(d)
87809-SU	LFX/CRD/6R/90CRI/3MW/5SCT/V2	13/19/27	1500/2100/3000	90	120-347	27K/30K/35K/40K/50K	50000	DL,DIM,ES	4.4(h) 8.25(d)
87810-SU	LFX/CRD/8R/90CRI/3MW/5SCT/V2	18/27/36	2000/3000/4000	90	120-347	27K/30K/35K/40K/50K	50000	DL,DIM,ES	4.75(h) 10.25(d)
87811-SU	LFX/CRD/9.5R/90CRI/3MW/5SCT/V2	20/30/40	2500/3750/5000	90	120-347	27K/30K/35K/40K/50K	50000	DL,DIM,ES	4.75(h) 11.2(d)

DIM = Dimmable **DL** = Rated Damp Location **ES** = Energy Star