



2 LONGHORSE 2

LH2-277-L

BALLAST SPECIFICATIONS

UL & cUL APPROVED (E186503) • PATENTED

INPUT


VOLTAGE	277 ± 10% VAC
FREQUENCY	50/60 Hz
MAXIMUM POWER	35 WATT
MAXIMUM CURRENT	.15 AMP
PROTECTION	
• OVER CURRENT	FUSE
• VOLTAGE TRANSIENTS	MOV (PER ANSI C82.11 - 1993)
EMI /RFI	FCC PART 18-A

OUTPUT

OPEN CIRCUIT VOLTAGE	600V RMS MAXIMUM
BALLAST MIN. STARTING TEMP.	-20°F
LAMP STARTING / TEMP	INSTANT START / SEE LAMP SPECIFICATIONS
PROTECTION	
• OPEN LAMP	YES
• SHORTED LAMP	YES

APPLICATION / MECHANICAL

RATED	TYPE 1 OR 2 OUTDOOR
BLACK / WHITE WIRES	18 INCHES
RED / YELLOW POWER WIRES	36 INCHES
CASE SIZE	H 1", W 1.72", L 9.5"
BALLAST WEIGHT	14.4 OZ
CASE QUANTITY	50 BALLASTS
CASE WEIGHT	45 lbs



LAMP COVERAGE

WHEN OPERATED IN ACCORDANCE WITH FULHAM'S WIRING CONFIGURATIONS

LINEAR LAMPS

T-5
T-5 HO
T-6
T-8

ONE OR MORE LAMPS

F4, F6, F8, F13, F14 or F21

ONE LAMP ONLY

F 28 or F35
F24
F42/F64
F13,F14, F15, F17, F18, F25, F30,
F32 or F72
F14, F15 or F20

COMPACT LAMPS

BX
FQD
QD
TB
2D
CIRCLINE

5W, 7W, 9W or 11W
10W or 13W
13W
10W

13W, 18W, 24W or 27W
18W, 24W or 36W
18W or 26W
18W, 26W or 32W
16W, 21W or 28W
20W or 22W

Fulham Co., Inc.

10/27/2008

12705 South Van Ness Ave.

TEL: 1.323.779.2980

www.Fulham.com

Hawthorne, CA 90250

FAX: 1.323.754.9060

info@fulham.com

Fulham Co., Inc.

2

**464 South Bedford Drive
Beverly Hills, CA 90212**

**TEL: 1.310.277.9484
FAX: 1.310.556.1263**

**www.Fulham.com
Fulham@earthlink.net**