PRODUCT DATASHEET
LEDVANCE HE BALLAST 2X39W T5 HO UNV PS N

T5 FLUORESCENT BALLASTS 120-277V | T5/T5HO programmed rapid start ballasts with low THD and universal 120-277V input



Product features

- High-efficiency operation with energy savings and long system life
- Universal 120–277V input for flexible applications
- Low THD and high power factor
- Compatible with ANSI-standard fluorescent lamp equivalents
- Backed by a five-year limited warranty

© 2026, LEDVANCE GmbH. All rights reserved.

TECHNICAL DATA

Additional product data

Ordering Abbreviation	LHE2X3924T5HOUNVPSN
Abbrev. With Packaging Info.	LHE2X3924T5HOUNVPSN 10/CS 1/SKU
SKU UPC	0046135758959
NAED	75895
General Description	High Efficiency 2x39 24 Ballast

Electrical data

Nominal voltage	120.00…277.00 V
Supply Frequency	50…60 Hz
Total Harmonic Distortion	< 10 %
Power factor	> 0.98

Dimensions & Weight

Length	9.5 in
Width	1.3 in
Height	1 in
Product weight	0.8 lb

Application & Mounting

Dimming	No
Maximum Case Temperature	70
Sound Rating	A
Wiring Method	leads

Capabilities

Dimming	No

Certificates & Standards

Certification Listing	RoHS / FCC / cULus / NRCAN

Logistical data

SKU Qty	1
Case Qty	10
Case Length (in)	10.866
Case Width (in)	9.882
Case Depth (in)	2.913
Case Cube (ft)	0.181
Case Weight (lbs)	8.571

© 2026, LEDVANCE GmbH. All rights reserved.

SKU UPC	0046135758959
Pallet Qty	1,200

DOWNLOAD DATA

	Spec Sheets and Product Documents	Document name
PDF	Certificates	LEDVANCE Ballast Limited Warranty
PDF	Product Family Spec Sheet	LEDVANCE T5HO & T5 Programmed Rapid Start ECS310

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

© 2026, LEDVANCE GmbH. All rights reserved.