


Model: 809

120V Track MR16 Luminaire

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Low Voltage luminaire with die-cast aluminum construction and swivel yoke for precise aiming.

FEATURES

- Available with LED lamp option
- Swivel yoke for easy aiming
- 350° horizontal rotation and 90° vertical tilt
- Mesh back vent for heat dissipation
- Clear lens included (Halogen version)
- Dimmable
- 5 year fixture warranty/3 year LED lamp warranty

SPECIFICATIONS

Construction: Die-cast aluminum track head with polycarbonate transformer case and track adapter. Bi-pin ceramic socket for MR16 lamp.

Finish: Powder coated Black (BK), White (WT), and Electroplated Brushed Nickel (BN).

Transformer: LED Version - 1W minimum load.
Halogen Version - 20W minimum load (1W minimum load available).
Consult factory for more details.

Lamp: 809 model uses 12V MR16, 50W max lamp (not included).
809L model uses 12V MR16, 75W max (not included).
809LED model uses a 12V, 8W MR16 LED lamp (included).
450 lumens, 3000K CCT, 25,000 hour rated life, CRI: 85.

Dimming: With electronic low voltage (ELV) dimmer, LED lamp dims to 10%;
Halogen lamp dims to 1%.

Standards: UL & CUL Listed.

ORDER NUMBER


System	Model #	Power	Lamp	Finish
LHT L Track	809LED*	8W	LED	BK Black
HHT H Track	809	50W	Halogen	BN Brushed Nickel
JHT J/J2 Track	809L	75W	Halogen	WT White



Example: **LHT-809LED-BN**

*Incompatible with lens accessories

FINISHES



ACCESSORIES

Color Lens	LENS-16-	AMB	Amber	UV Filter	LENS-16-UVF
		BLU	Blue	Frosted Lens	LENS-16-FR
		GRN	Green	Spread Lens	LENS-16-SPR
		RED	Red	Beam Elongating Lens	LENS-16-BEL
		YEL	Yellow	Honeycomb Louver	LENS-16-HCL

WAC Lighting

www.waclighting.com

Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive • Port Washington, NY 11050

Phone (516) 515.5000 • Fax (516) 515.5050

Western Distribution Center

1750 Archibald Avenue • Ontario, CA 91760

Phone (800) 526.2588 • Fax (800) 526.2585