



Type IC, Wet & Air-Tight

DESCRIPTION

3" Round Eyeball Recessed Gimbal LED
With Integral Driver In Connection Box
Gimbal Yet Air-Tight Without Housing Needed


FEATURES & BENEFITS

1 3/4" Deep - Install Where Ceiling Space Is Limited
Type IC Rated - No Housing Required
Driver Inside Connection Box - No Junction Box Needed
CRI 90+ for True Color Rendering
Available in single CCT, Dim to Warm, & 5CCT

MOUNTING

Cut Hole In Ceiling And Snap Fixture In Opening
With Attached Spring Clips
Ceiling Clearance Required: 3 1/2"

DIMENSIONS: ID 2 1/2" OD 3 1/4" Cut Out 2 3/4" to 3"



AVAILABLE TRIMS



White

Black

Brushed Nickel

ORDERING GUIDE Example: LL3G - 30K - WH

	CCT	Trim Finish	
LL3G	- xxK	- xx	
2700K	27K	WH	White
3000K	30K	BK	Black
3500K	35K	BN	Brushed Nickel
4100K	41K		
5000K	50K		
DTW 3K-2K	32K	Dim to Warm 3000K to 2000K	
5CCT	5CCT	User selectable 27-30-35-40-50K	

LL3G

3" Eyeball Round Recessed Gimbal LED 7.5W

Project:

Location:

Model #:

Qty:

Notes:

SPECIFICATION	
Applications	Sloped Ceilings up to 20°, General Lighting
Energy Used	7.5 W
Color Temperature	2700 3000 3500 4100 5000 DTW 5CCT
Light Output	580 600 620 630 650 500
Halogen Equivalent	50 W
Beam Angle	38° Beam with 20° tilt and 360° rotation
CRI	90 +
Default Driver Input	120V AC Triac Dimmable
Optional Driver Input	120V-347V AC 0-10V Dimmable
Junction Box Wire Capacity	Max 5 No 12 AWG or 8 No 14 AWG
Power Factor	0.95
Approved Location	Insulated Ceiling & Wet Locations
IP Rating	IP 54
Air Tight	Yes
Ambient Temperature	-40°F (-40°C) to +104°F (+40°C)
Projected Life	70% Light Output at 50,000 Hours
Certification	cULus, T24
Warranty	10 Year Residential / 5 Year Commercial

120V TRIAC Dimmable
Driver Included



Optional 120V-347V
Driver 0-10V Dimmable
Order Separately as
[model # LLL-LD0716T](#)



ACCESSORIES

Sold Separately



Low Voltage Extension Cables. Max 40 ft Allowed
[6ft - model # EXC6](#)
[20ft - model # EXC20](#)



[Flat Rough-In Plates - model # RIP3](#)



[Flanged Plate with Hanger Bars model # FRP3](#)



[Goof Ring OD 4 1/2" White # GR3 Black # GR3-BK](#)



Emergency Back Up Drivers
[model # BLD-HM08D-YYY](#)

Lotus LED Lights USA

250 H Street # 301, Blaine WA 98230 tel 360-200-5500
Hainesport NJ & Ferndale WA

www.LotusLEDLights.com

mailing addresses
warehouses

Lotus LED Lights CANADA

1080 Cliveden Ave # 6, Delta BC V3M 6G6 tel 604-538-3090
Delta BC & Mississauga ON