



**Product Number:** 67543

**Order Abbreviation:** LU1000/SBY

**General Description:** 1000W LUMALUX STANDBY high pressure sodium HID lamp, instant restrike, 40,000hrs avg rated life, E39 based, E25 bulb, universal burn, clear

#### Product Information

Abbrev. With Packaging Info.	LU1000SBY 6/CS 1/SKU
ANSI Code	S52
Approx. Lumens (initial - horizontal)	127000
Approx. Lumens (initial - vertical)	127000
Approx. Lumens (mean - horizontal)	115000
Approx. Lumens (mean - vertical)	115000
Arc Length (in)	8.12
Arc Length (mm)	206.2
Average Rated Life - Horizontal (hr)	30000
Average Rated Life - (hr)	30000
Avg Rated Life (hrs)	30000
Base	E39 Mogul
Bulb	E25
Color Rendering Index (CRI)	22
Color Temperature/CCT (K)	2100
Diameter (in)	3.100
Diameter (mm)	78.00
Family Brand Name	Lumalux® Standby
Fixture Requirement	O
Hot Restrike Time (min)	INSTANT
Lamp Finish	Clear
Light Center Length - LCL (in)	8.74
Light Center Length - LCL (mm)	222
Maximum Base Temperature - Fahrenheit	482
Maximum Base Temperature - Celsius	250
Maximum Bulb Temperature - Fahrenheit	752
Maximum Bulb Temperature - Celsius	400
Maximum Overall Length - MOL (in)	15.08
Maximum Overall Length - MOL (mm)	383
Nominal Voltage (V)	250.00
Nominal Wattage (W)	1000.00
Operating Position	Universal
Warm-up Time (min)	3-4 MINUTES

#### Footnotes

- Use with 5000V pulse rated sockets only.
- Mean lumens measured at 50% of average rated life