


Slide-to-off dimmers



- Higher capacity dimmers require larger heat sink behind wallplate
- Slide up to brighten, down to dim
- Measures 4.56 in x 4.56 in
- Requires large wallplate
- Most can fit in a 1-gang electrical backbox

 **Magnetic low-voltage and/or Neon/cold cathode dimmers***
(large controls)

Slide-to-off dimmers

Single-pole 120V 1000 VA (800W)	NLV-1000- XX ¹
Single-pole 120V 1500 VA (1200W)	NLV-1500- XX ¹


For neon/cold cathode dimming, consult Lutron Technical Support: Application note #25.

The stated VA (Volt-Ampere) rating includes the magnetic transformer heat losses and the lamp load. The stated W (Watt) rating is the maximum lamp wattage based on assumed 20% transformer loss.

 **Incandescent/halogen dimmers**
(large controls)

Slide-to-off dimmers

Single-pole 120V 1500W	N-1500- XX ¹
Single-pole 120V 2000W	N-2000- XX ¹

 **3-wire fluorescent dimmers***
(also for Hi-lume® A-Series LED drivers)
(large controls)

Slide-to-off dimmers

Single-pole 277V 8A	NF-10-277- XX ¹
------------------------	-----------------------------------

For use with EcoSystem®, Hi-lume 3D and Hi-lume ballasts, and Hi-lume A-Series LED drivers.

For more information on Hi-lume A-Series LED drivers, visit www.lutron.com/HilumeLED.

No derating required if ganged.

Adjustable low-end trim.

XX¹: Architectural matte color codes, see pg. 36 (1-gang wallplate included)

For more information on ballasts, visit www.lutron.com/ballasts.
Custom ganging and derating applies, see pg. 179.

*Requires neutral wire connection.