



LW Linear Wrap

FEATURES

- Ideal for storage areas, utility rooms, stairwells, corridors, and similar applications
- 2' and 4' versions
- Up to 111 lumens per watt
- High efficacy LED engine maximizes energy savings
- Full length wrap-around U-shaped prismatic acrylic lens
- FieldCCeT feature allows for multiple "set and forget" CCT options
- Internal back-up battery field install accessory available

CERTIFICATIONS

- UL Listed for dry/damp locations
- DesignLights Consortium® Qualified - meets DLC requirements for efficacy and lumen maintenance

PERFORMANCE

- Rated lifetime L70: 50,000 hours
- 4000K or FieldCCeT: 3500K/4000K/5000K selectable CCT
- CRI: >80 or >90

ELECTRICAL

- Input voltage: 120-277V
- 0-10V dimming (FieldCCeT models)
- Power Factor: >0.9
- THD: <20%

THERMAL

- -4°F to 104°F (-20°C to 40°C) operating temperature


CONSTRUCTION

- Durable steel body construction with white powder coat finish
- Max linkability:
 - LW2/20W/840/U: 20
 - LW4/40W/840/U: 10
 - LW4/27W/9FCCT3/UD: 15
 - LW4/36W/9FCCT3/UD: 11
 - LW4/45W/9FCCT3/UD: 9

WARRANTY

- 5 year limited warranty. Additional warranty options available. Contact EiKO for details

project name	type
catalog number	voltage
approved by	date



CONNECTORS INCLUDED

APPLICATIONS

- Storage areas
- Utility rooms
- Schools
- Stairwell
- Workshops
- Corridors

CONFIGURATOR

MODEL	WATTS/LUMENS	CRI/CCT	VOLTAGE	DIMMING
LW2 : Linear Wrap 2'	20W - 20W; 2,000 lm	840 - 80 CRI; 4000K	U - 120-277V	[Blank] - Non-Dimming
LW4 : Linear Wrap 4'	40W - 40W; 4,000 lm			
	27W - 27W; 3,000 lm	9FCCT3 - 90 CRI; 35/40/5000K		D - 0-10V Dimming
	36W - 36W; 4,000 lm			
	45W - 45W; 5,000 lm			



PERFORMANCE SUMMARY

ORDER CODE	ITEM #	SIZE	WATTS	NOMINAL LUMENS	LPW	CCT	CRI	DIMMING	VOLTS	MAX LINKABILITY	REPLACES	DLC STANDARD
11595	LW2/20W/840/U	2'	20W	2,000	100	4000K	>80	-	120-277V	20	2 lamp T8	
11596	LW4/40W/840/U	4'	40W	4,000	100	4000K	>80	-	120-277V	10	3 lamp T8	
11631	LW4/27W/9FCCT3/UD	4'	27W	3,000	111	35/40/5000K	>90	0-10V	120-277V	15	2 lamp T8	✓
11632	LW4/36W/9FCCT3/UD	4'	36W	4,000	111	35/40/5000K	>90	0-10V	120-277V	11	3 lamp T8	✓
11633	LW4/45W/9FCCT3/UD	4'	45W	5,000	111	35/40/5000K	>90	0-10V	120-277V	9	4 lamp T8	✓

ACCESSORIES

ORDER CODE	ITEM #	INPUT VOLTAGE	EMERGENCY TIME	OUTPUT POWER	RECHARGE TIME	TITLE 20
10918	EEBN08WUA050	120-277V	>90mins	8W	24 hrs	✓
10896	EEBN15WUA050	120-277V	>90mins	15W	24 hrs	✓
10897	EEBN20WUA050	120-277V	>90mins	20W	24 hrs	✓

*NOTE: 4ft models only. Accessories are not compatible with 2ft model

PRODUCT DIMENSIONS

