

## Large Wall Pack - LED

### Features

- Construction
  - One-piece die-cast aluminum housing and hinged, removable die-cast aluminum door
  - One-piece silicone gasket seals the optical chamber
  - Housing has a textured bronze finish
  - Borosilicate molded glass lens
  - 1/2" conduit access, sides, top, or rear knockouts
- Photocell adaptable and UL listed for wet locations
- LED driver and electrical components are mounted to the die-cast housing for optimal heat sinking and operating efficiency
- UL recognized integral LED electronic driver is Class 2 rated for 120-277V, 50/60Hz
- LEDs provide 80+ CRI in warm, neutral, and cool white colors
- 0-10V standard dimming capability
- The LED system delivers, on average, 70% of lumen maintenance (L70) at 100,000 hours
- Suitable for ambient temperature up to 55°C (131°F) for LWP-XX-55, LWP-XX-75 configurations and up to 45°C (113°F) for LWP-XX-90 configuration
- 5 Year warranty

Project:	
Catalog#:	
Approved by:	
Date:	



Classic look - modern performance



Ordering Information Sample Model: LWP-5055-LED-MV			
Series	Color	Configuration	Factory Installed Options (y)
LWP-	50	55-LED-MV	
LWP-	30: 3000K	55-LED-MV 6,600 Lumens, 53W	(blank): No FIO  -M: Microwave Motion Sensor
	40: 4000K	75-LED-MV 9,400 Lumens, 80W	
	50: 5000K	90-LED-MV 12,000 Lumens, 95W	

Note: Order with (-M) for title 24 compliance in CA

Cross Reference Chart				
Comparable to HID		LED Replacement		Energy Savings
Source	Input Watts <sup>1</sup>	Model #	Input Watts	Percentage
400W	464	LWP-5090-LED-MV	95	80%
250W	295	LWP-5075-LED-MV	80	73%
150W	185	LWP-5055-LED-MV	53	71%

<sup>1</sup>120V on Quad Tap Ballast



Accessories (sold separately)	
Catalog #	Description
LCPCM V	LED compatible external stem & swivel mount electronic photocontrol <sup>2</sup>

<sup>2</sup>Please use LED compatible electronic components to maintain warranty.

### Applications

Ideal for parking facilities, entry ways, perimeter/pathway lighting for underpasses.

### Dimensions





Proudly Assembled  
IN THE USA\*

### Online Resources



\*Foreign and domestic components.

## Photometric Details (Data shown for LWP-3075 model at a 12ft. mounting height)



**Illuminance at a Distance**

	Center Beam fc	Beam Width	
2.0ft	698.6 fc	5.3 ft	3.7 ft
4.0ft	174.6 fc	10.6 ft	7.5 ft
6.0ft	77.6 fc	15.9 ft	11.2 ft
8.0ft	43.7 fc	21.2 ft	14.9 ft
10.0ft	27.9 fc	26.5 ft	18.6 ft
12.0ft	19.4 fc	31.8 ft	22.4 ft

■ Vert. Spread: 105.8°  
■ Horiz. Spread: 86.0°

## Performance - Lighting Facts

