


PRISM SYNERGY MODS **G1** **24** VDC

High-performance 24V LED channel letter illumination



Specifications

Dimensions L x W x H	Micro	1.02" x 0.35" x 0.37"
	Mini	2.05" x 0.73" x 0.38"
	Spec	3.78" x 0.73" x 0.38"
	HO, Deep	4.25" x 0.73" x 0.38"
Beam angle	Micro, Mini,	170°
	Spec, HO	
	Deep	140°
Mounting options	Micro	Peel-N-Stick
	Mini, Spec,	Peel-N-Stick and mechanical
	HO, Deep	
Operating temp.		-40° C to +70° C
Environment		IP67
Wire color		White (+) / Gray (-)
Warranty		Life of Sign Warranty/10-year Limited Labor



Whites

Product	Mods per ft	Color temp.	SKU	Power	Intensity	Efficacy	Packaging	Max. mods/ series	Max. mods per 96 W power supply	UL number
Prism Synergy Micro	6	7100 K	M-SYMC0-71	0.286 W /mod	46.7 lm/mod (280 lm/ft)	163 lm/W	Mods per bag: 300 Mods per strand: 60 Strands per bag: 5 Bags per case: 16 Mods per case: 4800	120 mods	335 (55 ft)	PL-SY2-MC7-P
		6500 K	M-SYMC0-65							
		5000 K	M-SYMC0-50							
		4100 K	M-SYMC0-41							
		3000 K	M-SYMC0-30							
Prism Synergy Mini	1.8	7100 K	M-SYMN0-71	0.461 W /mod	72.0 lm/mod (130 lm/ft)	156 lm/W	Mods per bag: 200 Mods per strand: 50 Strands per bag: 4 Bags per case: 8 Mods per case: 1600	50 mods	208 (115 ft)	PL-SY2-MN2-P
		6500 K	M-SYMN0-65							
		5000 K	M-SYMN0-50							
		4100 K	M-SYMN0-41							
		3000 K	M-SYMN0-30							
Prism Synergy Spec	1.3	7100 K	M-SYSP0-71	0.888 W /mod	138.4 lm/mod (180 lm/ft)	156 lm/W	Mods per bag: 100 Mods per strand: 50 Strands per bag: 2 Bags per case: 10 Mods per case: 1000	50 mods	108 (83 ft)	PL-SY4-SP2-P
		6500 K	M-SYSP0-65							
		5000 K	M-SYSP0-50							
		4100 K	M-SYSP0-41							
		3000 K	M-SYSP0-30							
Prism Synergy HO	1.2	7100 K	M-SYHXX-71*	1.330 W /mod	208.5 lm/mod (250 lm/ft)	157 lm/W	Mods per bag: 72 Mods per strand: 36 Strands per bag: 2 Bags per case: 13 Mods per case: 936	36 mods	72 (60 ft)	PL-SY4-HO1-P
		6500 K	M-SYHXX-65*							
		5000 K	M-SYHXX-50*							
		4100 K	M-SYHXX-41*							
		3000 K	M-SYHXX-30*							
Prism Synergy Deep	1.8	7100 K	M-SYDPO-71	1.330 W /mod	208.5 lm/mod (375 lm/ft)	157 lm/W	Mods per bag: 72 Mods per strand: 36 Strands per bag: 2 Bags per case: 15 Mods per case: 1080	36 mods	72 (40 ft)	PL-SY4-DP2-P
		6500 K	M-SYDPO-65							
		5000 K	M-SYDPO-50							
		4100 K	M-SYDPO-41							
		3000 K	M-SYDPO-30							



* **XX** can be **00** (Gen 1, version 1), or **02** (Gen 1, version 2).

Specifications subject to change without notice.



PRISM SYNERGY MODS **G1** **24** VDC

High-performance 24V LED channel letter illumination



Specifications (cont.)

Colors

* Limited quantity on hand.

Product	Mods /ft	Color temp.	SKU	Power	Intensity	Efficacy	Packaging	Max. mods/ series	Max. mods per 96 W power supply	UL number
Prism Synergy Mini	1.8	Red	M-SYMNO-RD	0.461 W /mod	16.3 lm/mod (29 lm/ft)	35 lm/W	Mods per bag: 200 Mods per strand: 50 Strands per bag: 4 Bags per case: 8 Mods per case: 1600	50 mods	208 (115 ft)	PL-SY2-MN2-P
		Orange*	M-SYMNO-OR		21.0 lm/mod (37.8 lm/ft)	44 lm/W				
		Yellow*	M-SYMNO-YL		17.0 lm/mod (30.6 lm/ft)	35 lm/W				
		Green	M-SYMNO-GR		43.9 lm/mod (79 lm/ft)	95 lm/W				
		Blue	M-SYMNO-BL		9.8 lm/mod (18 lm/ft)	21 lm/W				
Prism Synergy Spec	1.3	Red	M-SYSP0-RD	0.888 W /mod	20.4 lm/mod (26 lm/ft)	23 lm/W	Mods per bag: 100 Mods per strand: 50 Strands per bag: 2 Bags per case: 10 Mods per case: 1000	50 mods	108 (83 ft)	PL-SY4-SP2-P
		Orange*	M-SYSP0-OR		51.0 lm/mod (66.3 lm/ft)	59 lm/W				
		Yellow*	M-SYSP0-YL		33.0 lm/mod (42.9 lm/ft)	37 lm/W				
		Green	M-SYSP0-GR		54.9 lm/mod (71 lm/ft)	62 lm/W				
		Blue	M-SYSP0-BL		11.9 lm/mod (15 lm/ft)	13 lm/W				

Life of Sign Warranty

- The Life of Sign Warranty only applies to the Prism Synergy modules in applications, not the power supply.
- The product warranty itself is the same as it is for all of our other products as outlined in the Principal Sloan Warranty Statement; only the duration of the coverage has changed.
- The lifetime product coverage will require the submission of the **Principal Sloan Warranty Registration Form** within 30 days of the installation of the sign.
- If the Warranty Registration Form is submitted within the specified 30-day period, the term of the coverage begins at the date of the sign installation.
- If the Warranty Registration Form is not submitted within the specified 30-day period, the term of the coverage begins at the manufacture date code on the products.
- The lifetime warranty will only apply to the original and unaltered sign
- For specification work, the warranty is with the OEM or National Program End-User per contract agreement to use the Prism Synergy Series.



PRISM SYNERGY MODS **G1** **24** VDC

High-performance 24V LED channel letter illumination



Recommended Coverage Charts

Channel Letters

Model	Depth	Mods/ft	Single stroke width	Multi-row on-center spacing
Prism Synergy Micro	1"	6	2.5"	1.5"
	2"		3"	2.5"
	3"		6"	5"
	4"			6"
Prism Synergy Mini	2"	2.5	6"	5"
	3"	2	9"	8"
	4"		12"	11"
	5"	2	15"	14"
Prism Synergy Spec	4"	1.5	13"	12"
	5"	1.3	17"	16"
	6"			
Prism Synergy HO	6"	1.2	16"	14"
	7"		17"	16"
	8"		18"	17"
Prism Synergy Deep	8"	2	17"	17"
	9"		18"	
	10"		20"	18"

Cabinets

Product	Depth from stik to face	Estimated spacing between stiks
Prism Synergy HO	8 - 14"	12"
	14 - 16"	16"
	16 - 18"	24"
	>18"	Use two banks of single-sided
Prism Synergy Deep	10 - 14"	12"
	14 - 18"	16"
	18 - 20"	24"
	>20"	Use two banks of single-sided

Product and depth may vary depending on face material and desired brightness.
All spacing guidelines in this chart were done using 7328 White Acrylic faces. Other materials, thicknesses, and color can affect these guidelines in your sign. To ensure accuracy, it is recommended that you test the product in your specific application in a dark setting prior to installation. If you have concerns or questions about the materials you are using for your application please contact us for assistance.