



Product Number: 64468

Order Abbreviation: M1000/U

General Description: 1000W METALARC quartz metal halide lamp, E39 base, BT56 bulb, enclosed fixture rated, universal burn, clear, 4000K

Product Information

| | |
|---------------------------------------|-------------------|
| Abbrev. With Packaging Info. | M1000U 6/CS 1/SKU |
| ANSI Code | M47/S |
| ANSI Code 2 | M47/S |
| Approx. Lumens (initial - horizontal) | 107800 |
| Approx. Lumens (initial - vertical) | 110000 |
| Approx. Lumens (mean - horizontal) | 86000 |
| Approx. Lumens (mean - vertical) | 86000 |
| Arc Length (in) | 3.58 |
| Arc Length (mm) | 91 |
| Average Rated Life - Horizontal (hr) | 12000 |
| Average Rated Life - (hr) | 12000 |
| Average Rated Life - Vertical (hr) | 18000 |
| Base | E39 Mogul |
| Bulb | BT56 |
| Color Rendering Index (CRI) | 65 |
| Color Temperature/CCT (K) | 4000 |
| Diameter (in) | 7.008 |
| Diameter (mm) | 178.00 |
| Family Brand Name | Metalarc® |
| Fixture Requirement | S |
| Hot Restrike Time (min) | 7-12 |
| Lamp Finish | Clear |
| Light Center Length - LCL (in) | 9.5 |
| Light Center Length - LCL (mm) | 241 |
| Maximum Base Temperature - Fahrenheit | 482 |
| Maximum Base Temperature - Celsius | 250 |
| Maximum Bulb Temperature - Fahrenheit | 752 |
| Maximum Bulb Temperature - Celsius | 400 |
| Maximum Overall Length - MOL (in) | 15.4 |
| Maximum Overall Length - MOL (mm) | 391 |
| Nominal Voltage (V) | 263.00 |
| Nominal Wattage (W) | 1000.00 |
| Operating Position | Universal |
| Warm-up Time (min) | 2-4 |