



**Product Number:** 64457  
**Order Abbreviation:** M250/U  
**General Description:** 250W METALARC quartz metal halide lamp, E39 base, BT28 bulb, enclosed fixture rated, universal burn, clear, 4200K

#### Product Information

Abbrev. With Packaging Info.	M250U 6/CS 1/SKU
Approx. Lumens (initial - horizontal)	20000
Approx. Lumens (initial - vertical)	22000
Approx. Lumens (mean - horizontal)	13000
Approx. Lumens (mean - vertical)	15000
Arc Length (in)	1.38
Arc Length (mm)	35
Average Rated Life - Horizontal (hr)	10000
Average Rated Life - (hr)	10000
Average Rated Life - Vertical (hr)	10000
Base	E39 Mogul
Bulb	BT28
Color Rendering Index (CRI)	65
Color Temperature/CCT (K)	4200
Diameter (in)	0.000
Diameter (mm)	0.00
Family Brand Name	Metalarc®
Fixture Requirement	E
Hot Restrike Time (min)	7-12
Lamp Finish	Clear
Light Center Length - LCL (in)	5
Light Center Length - LCL (mm)	127
Maximum Base Temperature - Fahrenheit	482
Maximum Base Temperature - Celsius	250
Maximum Bulb Temperature - Fahrenheit	752
Maximum Bulb Temperature - Celsius	400
Maximum Overall Length - MOL (in)	8.31
Maximum Overall Length - MOL (mm)	211
Nominal Wattage (W)	250.00
Operating Position	Universal
Warm-up Time (min)	2-4