



MASTER Glass LED bulbs

MAS LEDBulbDT3.4-40WB22 927A60CL G UK

Featuring a classic heritage design, these filament MASTER glass bulbs combine the familiar shapes of incandescent glass LED bulbs with the benefits of long-lasting LED technology. Ideal for creating a cosy atmosphere for customers, these glass LED bulbs provide excellent quality of light. MASTER glass bulbs can be dimmed for different lumen levels and colour temperatures (dimmable glass led bulbs). They also deliver significant energy savings, using 30% less energy compared to normal LED bulbs. By offering a lifetime of 25,000 hours, these dimmable glass LED bulbs also reduce maintenance costs.

Product data

General information	
Cap base	B22 [B22]
EU RoHS compliant	Yes
Nominal lifetime (nom.)	25000 h
Switching cycle	20,000X
	Sphere
Tier	MASTER
Light technical	
Colour Code	922-927 [CCT of 2,200 K-2,700 K]
Luminous flux (nom.)	470 lm
Colour designation	Warm Glow (WG)
Correlated Colour Temperature (Nom)	2200 2700 K
Luminous efficacy (rated) (nom.)	138 lm/W
Colour consistency	<6
Colour rendering index (nom.)	90

LLMF at end of nominal lifetime (nom.)	70 %
Operating and electrical	
Input frequency	50 to 60 Hz
Power (Rated) (Nom)	3.4 W
Lamp current (nom.)	24 mA
Wattage equivalent	40 W
Starting time (nom.)	0.5 s
Warm-up time to 60% light (nom.)	0.5 s
Power factor (nom.)	0.6
Voltage (Nom)	220-240 V
Temperature	
T-ambient (max.)	45 °C
T-ambient (min.)	-20 °C
T-Case maximum (nom.)	70 °C

MASTER Glass LED bulbs

Controls and dimming

Dimmable Only with specific dimmers

Mechanical and housing

Lamp Finish Clear
Bulb material Glass
Bulb shape A60 [A 60mm]


Approval and application

Energy Efficiency Class D
Energy consumption kWh/1,000 hours 4 kWh
 1109130

Product data

Full product code 871951446655500
Order product name MAS LEDBulbDT3.4-40WB22 927A60CL G UK
EAN/UPC – product 8719514466555
Order code 46655500
SAP numerator – quantity per pack 1
Numerator – packs per outer box 10
SAP material 929003010142
Net Weight (Piece) 0.030 kg


Dimensional drawing




MAS LEDBulbDT3.4-40WB22 927A60CL G UK

Product	D	C
MAS LEDBulbDT3.4-40WB22 927A60CL G UK	60 mm	103 mm

Photometric data



Spectral Power Distribution Colour



Light Distribution Diagram

