

You are here [Litetronics Products](#) > [5-Watt Micro-Brite Cold Cathode R20 MED LO Frost Flood 2850K](#)

5-Watt Micro-Brite Cold Cathode R20 MED LO Frost Flood 2850K



Litetronics.com



MICRO-BRITE™

Markets

- Restaurants
- Hospitality
- Casino
- Cinema

Applications

- Dimmable Fixtures
- Elevators
- Recessed Cans
- Signs
- Track Lighting

Product Description

Micro-Brite cold cathode light bulbs are dimmable down to 5% of their light output. They provide smooth dimming control that works just like incandescent on standard dimmers, so no additional equipment is necessary. They can also be used in flashing signs without shortening their super long 25,000-hour life.

This 5-watt R20 Micro-Brite light bulb has a frost finish and can replace a 30-watt R20 incandescent bulb to provide up to 85% energy savings. It has a warm 2850K color temperature and fits in existing recessed cans and track heads.

Literature

- [Material Safety Data Sheet](#)
- [Micro-Brite Reflectors Enlightening Sheet](#)
- [Restaurant Brochure](#)
- [Cinema Brochure](#)
- [Casino Brochure](#)

[Contact a Litetronics Representative](#)

Specifications

| | |
|-------------------------------|--------------|
| Category | Cold Cathode |
| Shape | R20 |
| Brand | Micro-Brite |
| Part Number | MB-509DP |
| Watts | 5 |
| Base | MED LO |
| Voltage | 120 |
| Average Rated Life | 25,000 |
| Case Quantity | 15 |
| Initial Lumens | 200 |
| CRI | 82 |
| Color Temp | 2850K |
| Finish | Frost |
| Beam Angle | Flood |
| Burn Position | Universal |
| M.O.L. | 4.05" |
| Operating Temp | 5°F - 105°F |
| Power Factor | > .90 |
| THD % | < 30% |
| Incandescent Equivalent | 30 watts |
| Energy Savings (Incandescent) | \$68 |

CUSTOMER REVIEWS:

There are yet no reviews for this product.
Please log in to write a review.