



Product Number: 64265

Order Abbreviation: MCP39/PAR20/U/830/FL PB

General Description: 39W high CRI, powerball arc tube, reduced color shift, high performance, open rated, Par 20 Metal Halide Lamp, flood

Product Information

Abbrev. With Packaging Info.	MCP39PAR20U830FLPB 12/CS 1/SKU
ANSI Code	C130/O
Approx. Lumens (initial - horizontal)	2000
Average Rated Life - Horizontal (hr)	12000
Average Rated Life - (hr)	12000
Average Rated Life - Vertical (hr)	12000
Base	E26 Medium
Beam Angle (deg)	30
Bulb	PAR20
Color Temperature/CCT (K)	3000
Diameter (in)	2.480
Diameter (mm)	63.00
Family Brand Name	Metalarc® Powerball
Lamp Finish	Clear
Nominal Voltage (V)	90.00
Nominal Wattage (W)	39.00



Footnotes

- Consult your OSRAM SYLVANIA Lighting Representative for compatible electronic operating systems.
- Use with 4000V pulse rated sockets only.
- O = Lamps classified as O-type, comply with ANSI standard C78.389 for containment testing and may be used in open luminaries. See lamp warning.
- The circuit must include overcurrent protection (I.e. Thermally switched ballast).
- Lamp requires a nominal Open Circuit Voltage of 230V or higher. Without an ignitor in the circuit minimum OCV is 209Vrms.
- UV-Stop quartz

- Approved electronic ballast is required, view approved ballast list in Product documents, graphs and images.