

MDF036

Wall Sconce



Features

Housing

Die-formed Cold-rolled Steel

Finish Option: -62 Satin Nickel -30 Oil Rubbed Bronze

Optical

Shade: High Transmission Glass Creates Excellent Light Distribution and Uniformity

LED: High Efficiency, High CRI, Binned and Mixed to Reach Uniform Light

Electrical

High Power Factor, Low THD

-EM: Built-in Emergency Light

Lamp

LED Type: Integrate LED Module , 3000K LED

More Color Temperature Option 3500K, 4000K, 5000K

GU24 Type: - CFL Bulb, 2700K or 4000K


- 9W LED Bulb, 3000K or 4000K

Certification

UL/cUL or ETL/cETL Listed, Suitable for Damp Locations

Warranty

5 Years Limited Warranty on Driver and LED



LED Type

Model	Input Voltage	Input Wattage	LED CT	CRI	Lumen (TYP)	Finish/Shade	Dimension (W x H x D)	Energy Star
MDF036D-xxxxK	120V-277V	22W	3000K	>80	1850	Satin Nickel / Frosted Glass	12.0" x 12.0" x 4.0"	Yes
MDF036D-EM-xxxxK	120V-277V	22W	3000K	>80	1850	Satin Nickel / Frosted Glass	12.0" x 12.0" x 4.0"	---

GU24 Type

Model	Input Voltage	Lamp	Finish	Shade	Dimension (W x H x D)	Energy Star
MDF036PG-213	120V	2 x 13W GU24	Satin Nickel	Frosted Glass	12.0" x 12.0" x 4.0"	---