

# MDF039

## Wall Sconce



### Features

#### Housing

Die-formed Cold-rolled Steel

Finish Option: -62 Satin Nickel -30 Oil Rubbed Bronze

#### Optical

Shade: High Transmission Acrylic Creates Excellent Light Distribution and Uniformity

LED: High Efficiency, High CRI, Binned and Mixed to Reach Uniform Light

#### Electrical

High Power Factor, Low THD

#### Lamp

LED Type: Integrate LED Module , 3000K LED


More Color Temperature Option 3500K, 4000K, 5000K

GU24 Type: - CFL Bulb, 2700K or 4000K

- 9W LED Bulb, 3000K or 4000K

#### Certification

ETL/ETL Listed, Suitable for Damp Locations



### LED Type

| Model            | Input Voltage | Input Wattage | CT    | Lumen (Typ) | Finish       | Dimension (W x H x D) | Energy Star |
|------------------|---------------|---------------|-------|-------------|--------------|-----------------------|-------------|
| MDF039D-xxxxK-62 | 120V-277V     | 14W           | 3000K | 1360        | Satin Nickel | 16.0" x 7.9" x 4.0"   | Yes         |

### CFL Type

| Model      | Input Voltage | Lamp       | Finish       | Shade   | Dimension (W x H x D) | Energy Star |
|------------|---------------|------------|--------------|---------|-----------------------|-------------|
| MDF039-213 | 120V          | 2x13W GU24 | Satin Nickel | Acrylic | 16.0" x 7.9" x 4.0"   | ---         |