

Standard Metal Halide

HID

HALOGEN

CFL

FL

BALLAST

GERMICIDAL

| Product Information | | | | | | | Physical Information | | | | Photometric Characteristics | | | | | |
|---------------------|------|------|-------|------------------|-------|-----------|----------------------|--------------------|----------|----------|-----------------------------|------------------|-----------------|----------------|-----|--------------|
| Watts | Bulb | Base | Item# | Description | ANSI | Case Qty. | Finish | Operating Position | MOL (in) | LCL (in) | Initial Lumens (lm) | Mean Lumens (lm) | Avg. Life (Hrs) | Color Temp (K) | CRI | UPC |
| 70 | T6 | RX7s | 1045 | MHDE70/UVS/3K | M85/E | 12 | Clear | HOR ±15° | 4.63 | 2.24 | 5500 | 4250 | 12000 | 3200 | 65 | 844366010453 |
| 70 | T6 | RX7s | 1046 | MHDE70/UVS/4K | M85/E | 12 | Clear | HOR ±15° | 4.63 | 2.24 | 5500 | 4250 | 12000 | 4200 | 60 | 844366010460 |
| 70 | T6 | RX7s | 1081 | MHDE70/UVS/5K | M85/E | 12 | Clear | HOR ±15° | 4.63 | 2.24 | 4600 | 3900 | 12000 | 5200 | 70 | 844366010811 |
| 100 | T6 | RX7s | 1082 | MHDE100/UVS/3K | M90/E | 12 | Clear | HOR ±15° | 4.63 | 2.24 | 8500 | 7500 | 12000 | 3200 | 65 | 844366010828 |
| 100 | T6 | RX7s | 1066 | MHDE100/UVS/4K | M90/E | 12 | Clear | HOR ±15° | 4.63 | 2.24 | 8500 | 7500 | 12000 | 4200 | 60 | 844366010668 |
| 100 | T6 | RX7s | 1083 | MHDE100/UVS/5K | M90/E | 12 | Clear | HOR ±15° | 4.63 | 2.24 | 8000 | 6800 | 12000 | 5200 | 70 | 844366010835 |
| 150 | T7 | RX7s | 1047 | MHDE150/UVS/3K | M81/E | 12 | Clear | HOR ±15° | 5.33 | 2.60 | 13500 | 10625 | 12000 | 3200 | 65 | 844366010477 |
| 150 | T7 | RX7s | 1048 | MHDE150/UVS/4K | M81/E | 12 | Clear | HOR ±15° | 5.33 | 2.60 | 13500 | 10625 | 12000 | 4200 | 60 | 844366010484 |
| 150 | T7 | RX7s | 1084 | MHDE150/UVS/5K | M81/E | 12 | Clear | HOR ±15° | 5.33 | 2.60 | 10000 | 8500 | 12000 | 5200 | 70 | 844366010842 |
| 250 | T9.5 | Fc2 | 1085 | MHDE250/UVS/4K | M80/E | 12 | Clear | HOR ±15° | 5.33 | 2.60 | 20000 | 17000 | 10000 | 4200 | 60 | 844366010859 |
| 400 | T9.5 | Fc2 | 1086 | MHDE400/UVS/4K | M59/E | 12 | Clear | HOR ±15° | 5.33 | 2.60 | 28000 | 23800 | 10000 | 4200 | 60 | 844366010866 |
| 70 | T7.5 | G12 | 1087 | MH70/G12/UVS/3K | M85/E | 12 | Clear | Universal | 5.33 | 2.60 | 6000 | 5100 | 9000 | 3200 | 65 | 844366010873 |
| 70 | T7.5 | G12 | 1049 | MH70/G12/UVS/4K | M85/E | 12 | Clear | Universal | 5.33 | 2.60 | 6000 | 5100 | 9000 | 4200 | 65 | 844366010491 |
| 100 | T7.5 | G12 | 1088 | MH100/G12/UVS/3K | M90/E | 12 | Clear | Universal | 5.33 | 2.60 | 9000 | 7650 | 9000 | 3200 | 65 | 844366010880 |
| 100 | T7.5 | G12 | 1050 | MH100/G12/UVS/4K | M90/E | 12 | Clear | Universal | 5.33 | 2.60 | 9000 | 7650 | 9000 | 4200 | 65 | 844366010507 |
| 150 | T7.5 | G12 | 1089 | MH150/G12/UVS/3K | M81/E | 12 | Clear | Universal | 5.33 | 2.60 | 14000 | 9000 | 9000 | 3200 | 65 | 844366010897 |
| 150 | T7.5 | G12 | 1051 | MH150/G12/UVS/4K | M81/E | 12 | Clear | Universal | 5.33 | 2.60 | 14000 | 9000 | 9000 | 4200 | 65 | 844366010514 |