

HIGH INTENSITY DISCHARGE

Metal Halide for Aquarium ■■■

Product Information							Physical Information				Photometric Characteristics						
Watts	Bulb	Base	Item#	Description	ANSI	ANSI 2	Case Qty.	Finish	Operating Position	MOL (in)	LCL (in)	Initial Lumens (lm)	Mean Lumens (lm)	Avg. Life (Hrs)	Color Temp (K)	CRI	UPC
70	T6	RX7s	1140	MHDE70/UVS/10K	M85/E		12	Clear	HOR ±15°	4.63		3100		6000	10000	75	844366011405
70	T6	RX7s	1141	MHDE70/UVS/20K	M85/E		12	Clear	HOR ±15°	4.63		3100		6000	20000	75	844366011412
150	T7	RX7s	1142	MHDE150/UVS/10K	M81/E		12	Clear	HOR ±15°	5.33		7000	6000	10000	85		844366011429
150	T7	RX7s	1143	MHDE150/UVS/14K	M81/E		12	Clear	HOR ±15°	5.33		7000		6000	14000	65	844366011436
150	T7	RX7s	1144	MHDE150/UVS/20K	M81/E		12	Clear	HOR ±15°	5.33		7000		6000	20000	75	844366011443
175	T15	E39	2400	MH175/T15/HOR/10K	M57/E		24	Clear	HOR ±15°	5.00	5.00	7500		6000	10000	85	844366024009
175	T15	E39	2401	MH175/T15/HOR/14K	M57/E		24	Clear	HOR ±15°	5.00	5.00	7500		6000	14000		844366024016
175	T15	E39	2402	MH175/T15/HOR/20K	M57/E		24	Clear	HOR ±15°	5.00	5.00	7500		6000	20000		844366024023
250	T9.5	Fc2	2409	MHDE250/UVS/10K	M80/E		12	Clear	HOR ±15°	6.40	0.00	11000		6000	10000	85	844366024092
250	T9.5	Fc2	2410	MHDE250/UVS/14K	M80/E		12	Clear	HOR ±15°	6.40	0.00	11000		6000	14000	65	844366024108
250	T9.5	Fc2	2411	MHDE250/UVS/20K	M80/E		12	Clear	HOR ±15°	6.40	0.00	11000		6000	20000	75	844366024115
250	T15	E39	2403	MH250/T15/HOR/10K	M58/E		24	Clear	HOR ±15°	8.31	5.00	10500		8000	10000	85	844366024030
250	T15	E39	2404	MH250/T15/HOR/14K	M58/E		24	Clear	HOR ±15°	8.31	5.00	10500		8000	14000		844366024047
250	T15	E39	2405	MH250/T15/HOR/20K	M58/E		24	Clear	HOR ±15°	8.31	5.00	10500		8000	20000		844366024054
400	T15	E39	2406	MH400/T15/HOR/10K	M59/E		24	Clear	HOR ±15°	9.76	5.75	18500		8000	10000	85	844366024061
400	T15	E39	2407	MH400/T15/HOR/14K	M59/E		24	Clear	HOR ±15°	9.76	5.75	18500		8000	14000		844366024078
400	T15	E39	2408	MH400/T15/HOR/20K	M59/E		24	Clear	HOR ±15°	9.76	5.75	18500		8000	20000		844366024085
400	ET18	E39	2412	MH400/ET18/HOR/10K	M59/E		24	Clear	HOR ±15°	9.65	5.70	18500		8000	10000	85	844366024122
1000	ET25	E39	2413	MH1000/ET25/HOR/10K	M47/E		12	Clear	HOR ±15°	15.06	8.75	46000		3000	10000	85	844366024139

HID

HALOGEN

CFL

FL

BALLAST

GERMICIDAL