



**ProLume.**  
◀ Metal Halide

H.I.D.

## **ProLume.** Standard Metal Halide

### Energy Efficient

- High efficacy, up to 110 lumens per watt

### Technical Data

- 175 to 1500 watts
- Clear and coated
- 3700-4000K
- Improved color rendering compared to HPS
- Long life - Up to 20,000 Hours Average Rated Life


### Benefits

- Better light quality and more efficient than High Pressure Sodium or Mercury Vapor
- Unaffected by ambient temperature, suitable for indoor and outdoor use
- Consistent lamp to lamp color

**Shatter Proof lamps are available in 175, 250 and 400 watts.**

### Applications

- Industrial/Commercial
- Municipal lighting
- Retail
- Security lighting
- Street lighting




# ProLume Standard Metal Halide

Catalog Number: \_\_\_\_\_ Type: \_\_\_\_\_  
 Project: \_\_\_\_\_  
 Comments: \_\_\_\_\_ Date: \_\_\_\_\_  
 Prepared By: \_\_\_\_\_

HIGH INTENSITY DISCHARGE

Bulb Type	Watts	Base	Item #	Product Code	Description	Fixture Type	Inner/Master	ANSI Ballast Type	Initial Lumens	Avg Rated Life	MOL (Inches)	Color Temp	CRI
ED28	175	Mog	108200	MH175/U	Clear	E	1/12	M57/E	15200	10000	8.25"	4000	65
ED17	175	Med.	108262	MH175/U/MED	Clear	E	1/12	M57/E	15000	10000	5.45"	4000	65
ED28	175	Mog	108202	MH175/C/U	Coated	E	1/12	M57/E	14800	10000	8.25"	3700	70
ED17	175	Med.	108264	MH175/C/U/MED	Coated	E	1/12	M57/E	14800	10000	5.45"	3700	70
ED28	250	Mog	108204	MH250/U	Clear	E	1/12	M58/E	21000	10000	8.25"	4000	65
ED28	250	Mog	108604	MH250/U/CSTF	Clear PFA	E	1/12	M58/E	21000	10000	8.25"	4000	65
ED28	250	Mog	60303	MH250/HOR	Clear	E	1/12	M58/E	23000	10000	8.25"	4000	65
T15	250	Mog	108220	MH250/HBU/T15	Clear	E	1/12	M58/E	21000	10000	8.30"	4000	65
ED28	250	Mog	108206	MH250/C/U	Coated	E	1/12	M58/E	20000	10000	8.25"	3700	70
ED28	250	Mog	60302	MH250/C/HOR	Coated	E	1/12	M58/E	22000	10000	8.25"	3700	70
ED37	360	Mog	108212	MH360/BU/ES	Clear	E	1/6	M165/E M59/E	36000	20000	11.50"	4300	65
ED37	400	Mog	108208	MH400/U	Clear	E	1/6	M59/E	36000	20000	11.50"	4000	65
ED37	400	Mog	108600	MH400/U/CSTF	Clear PFA	E	1/6	M59/E	36000	20000	11.50"	4000	65
ED28	400	Mog	108216	MH400/U/ED28	Clear	E	1/12	M59/E	36000	20000	8.25"	4000	65
ED37	400	Mog	61201	MH400/BU/LU	LU Retrofit	E	1/12	S51/E	38000	10000	11.50"	4000	65
ED18	400	Mog	108218	MH400/HBU/ED18	Clear	E	1/12	M59/E	36000	20000	9.75"	4000	65
ED37	400	Mog	60301	MH400/C/HOR	Coated	E	1/6	M59/E	36800	20000	11.50"	3700	70
ED28	400	Mog	60201	MH400/C/U/ED28	Coated	E	1/12	M59/E	34000	20000	8.25"	3700	70
ED37	400	Mog	108210	MH400/C/U	Coated	E	1/6	M59/E	34000	20000	11.50"	3700	70
BT56	1000	Mog	108222	MH1000/U	Clear	E	1/6	M47/E	110000	12000	15.40"	4000	65
BT37	1000	Mog	108226	MH1000/U/BT37	Clear	E	1/6	M47/E	110000	12000	11.50"	4000	65
BT56	1500	Mog	108214	MH1500/BU	Clear	E	1/6	M48/E	161000	3000	15.40"	3400	65

 Hg-LAMP CONTAINS MERCURY, MANAGE IN ACCORD WITH DISPOSAL LAWS.  
 Visit [www.lamprecycle.org](http://www.lamprecycle.org) for disposal information for your state or local government.

WARNING: This lamp can cause serious skin burn and eye inflammation from shortwave ultraviolet radiation if outer envelope of the lamp is broken or punctured. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available. This lamp complies with FDA radiation performance standard 21 CFR subchapter J.