

■ ■ ■ Reflector Metal Halide

HID

HALOGEN

CFL

FL

BALLAST

GERMICIDAL

Product Information							Physical Information			Photometric Characteristics					
Watts	Bulb	Base	Item#	Description	ANSI	Case Qty.	Finish	Operating Position	MOL (in)	Beam Angle	CBCP (cd)	Avg. Life (Hrs)	Color Temp (K)	CRI	UPC
70	R40	E26	1058	MH70/R40/C/U/70°	M98/E	12	Coated	Universal	7.48	-	2300	10000	4000	60	844366010583
100	R40	E26	1059	MH100/R40/C/U/70°	M90/E	12	Coated	Universal	7.48	-	3300	10000	4000	60	844366010590
150	R40	E26	1105	MH150/R40/C/U/70°	M102/E	12	Coated	Universal	7.48	-	5200	10000	4000	60	844366011054
175	R40	E26	1060	MH175/R40/C/U/70°	M57/E	12	Coated	Universal	7.48	-	6500	10000	4000	60	844366010606
70	PAR30LN	E26	1067	MH70/PAR30LN/FL/3K	M98/E	12	Clear	Universal	4.72	50°	-	6000	3200	60	844366010675
70	PAR30LN	E26	1068	MH70/PAR30LN/FL/4K	M98/E	12	Clear	Universal	4.72	50°	-	6000	4200	60	844366010682
70	PAR38	E26	1061	MH70/PAR38/U/FL/3K	M98/E	12	Clear	Universal	5.35	60°	-	6000	3200	60	844366010613
70	PAR38	E26	1062	MH70/PAR38/U/FL/4K	M98/E	12	Clear	Universal	5.35	60°	-	6000	4200	60	844366010620
100	PAR38	E26	1063	MH100/PAR38/U/FL/3K	M90/E	12	Clear	Universal	5.35	60°	-	6000	3200	60	844366010637
100	PAR38	E26	1064	MH100/PAR38/U/SP/4K	M90/E	12	Clear	Universal	5.35	20°	-	6000	4200	60	844366010644
100	PAR38	E26	1065	MH100/PAR38/U/FL/4K	M90/E	12	Clear	Universal	5.35	50°	-	6000	4200	60	844366010651