



Switch Start Metal Halide Protected

MH 70W/640 E26 CL 1SL/24

An efficient, protected "O" rated lighting solution that is suitable for open-rated fixtures. Ideal for both indoor and outdoor applications.

Product data

General Information	
Base	E26 [Single Contact Medium Screw]
Operating Position	Base Up [Base Up]
Life to 5% Failures (Nom)	2000 h
Life to 50% Failures (Nom)	12000 h
System Description	na [-]

Light Technical	
Color Code	640 [CCT of 4000K]
Luminous Flux (Rated) (Min)	4200 lm
Luminous Flux (Rated) (Nom)	5600 lm
Color Designation	Cool White (CW)
Lumen Maintenance 2000 h (Nom)	73 %
Chromaticity Coordinate X (Nom)	385
Chromaticity Coordinate Y (Nom)	390
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	80 lm/W
Color Rendering Index (Nom)	60

Operating and Electrical	
Power (Rated) (Max)	- W
Power (Rated) (Min)	- W

Power (Rated) (Nom)	70.0 W
Lamp Current Run-Up (Max)	1.5 A
Lamp Current (EM) (Nom)	0.98 A
Ignition Supply Voltage (Max)	198 V
Ignition Supply Voltage (Min)	198 V
Voltage (Max)	100 V
Voltage (Min)	75 V
Voltage (Nom)	85 V

Controls and Dimming	
Dimmable	No

Mechanical and Housing	
Bulb Finish	Clear (CL)

Approval and Application	
Mercury (Hg) Content (Nom)	12 mg

Luminaire Design Requirements	
Bulb Temperature (Max)	450 °C
Cap-Base Temperature (Max)	250 °C

Switch Start Metal Halide Protected


Product Data	
Order product name	MH 70W/640 E26 CL 1SL/24
EAN/UPC - Product	046677137502
Order code	137505
Numerator - Quantity Per Pack	1

Numerator - Packs per outer box	24
Material Nr. (12NC)	928485800191
Net Weight (Piece)	0.075 kg

Warnings and Safety

- R "WARNING: These lamps can cause serious skin burn and eye inflammation from short wave ultraviolet radiation if outer envelope of the lamp is broken or punctured. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Certain lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available." This lamp complies with FDA radiation performance standard 21 CFR subchapter J. (USA:21 CFR 1040.30 Canada: SOR/DORS/80-381)
- Lamp contains mercury. Manage in Accord with Disposal Laws. See: www.lamprecycle.org or 1-800-555-0050

Dimensional drawing



MH 70W E26 ED17 CL

Product	D (max)	L (min)	C (max)
MH 70W/640 E26 CL 1SL/24	56 mm	83 mm	138 mm

