



Product Number: 64733
Order Abbreviation: MP175/BU-ONLY/MED
General Description: 175W open fixture rated metal halide lamp, clear, base up burn within 15deg

Product Information

| | |
|---------------------------------------|----------------------------|
| Abbrev. With Packaging Info. | MP175BUONLYMED 20/CS 1/SKU |
| ANSI Code | M57/O |
| Approx. Lumens (initial - vertical) | 14400 |
| Approx. Lumens (mean - vertical) | 8600 |
| Arc Length (in) | 0.71 |
| Arc Length (mm) | 18 |
| Average Rated Life - Vertical (hr) | 10000 |
| Avg Rated Life (hrs) | 10000 |
| Base | E26 Medium |
| Bulb | ED17 |
| Color Rendering Index (CRI) | 65 |
| Color Temperature/CCT (K) | 3600 |
| Diameter (in) | 2.126 |
| Diameter (mm) | 54.00 |
| Family Brand Name | Metalarc Pro-Tech® |
| Fixture Requirement | O |
| Hot Restrike Time (min) | 7-12 |
| Lamp Finish | Clear |
| Light Center Length - LCL (in) | 3.39 |
| Light Center Length - LCL (mm) | 86 |
| Maximum Base Temperature - Fahrenheit | 410 |
| Maximum Base Temperature - Celsius | 210 |
| Maximum Bulb Temperature - Fahrenheit | 752 |
| Maximum Bulb Temperature - Celsius | 400 |
| Maximum Overall Length - MOL (in) | 5.43 |
| Maximum Overall Length - MOL (mm) | 138 |
| Nominal Voltage (V) | 132.00 |
| Nominal Wattage (W) | 175.00 |
| Operating Position | BASE UP WITHIN 15DEG ONLY |
| Warm-up Time (min) | 2-4 |

Footnotes

- O = Lamps classified as O-type, comply with ANSI standard C78.389 for containment testing and may be used in open luminaries. See lamp warning.