



PRISM®  
 < MR11

## PRISM® MR11



### Technical Data

- 2900K
- Cool beam dichroic reflector
- Protective glass lens for operation in open or enclosed fixtures
- Integrated UV protection
- 24 volt lamps use half the current of 12 volt systems, allowing higher wattage loads and up to twice as many lamps on one transformer
- High lumen maintenance - over 90% throughout lamp life

### Benefits

- Compact light source
- White light
- Greatly reduces fading caused by UV exposure

### Applications

- Decorative lighting
- Accent lighting
- Display lighting
- Landscape lighting

### ISO 9001 Certified

Call Halco today and get a great look at our vast product line, personal service and fast delivery. Visit us at [halcolighting.com](http://halcolighting.com).

Your account representative is your single source for pricing, orders, and technical support.

Shipping from Atlanta, Cleveland, Houston, and Phoenix.



where there's light,  
 there's halco™

(800) 677-3334  
[halcolighting.com](http://halcolighting.com)

Bulb Type	Watts	Base	Item #	Product Code	Description	Inner/ Master	Volts	Color Temp	Center Candlepower	Avg Rated Life	Filament Design	MOL	Beam Spread
<b>12 VOLT BI-PIN</b>													
MR-11	5	GU4	107516	MR11FL5/L	FL w/Lens	10/200	12	2900	80	3000	C-6	1-3/8"	30°
MR-11	10	GU4	107940	MR11FL10/L	FL w/Lens	10/200	12	2900	300	3000	C-6	1-3/8"	30°
MR-11	10	GU4	107114	MR11SP10/L	SP w/Lens	10/200	12	2900	2500	3000	C-6	1-3/8"	10°
MR-11	20	GU4	107100	MR11FTB/L	NSP w/Lens	10/200	12	2900	5500	3000	C-6	1-3/8"	10°
MR-11	20	GU4	107102	MR11FTC/L	MFL w/Lens	10/200	12	2900	1750	3000	C-6	1-3/8"	20°
MR-11	20	GU4	107104	MR11FTD/L	FL w/Lens	10/200	12	2900	700	3000	C-6	1-3/8"	30°
MR-11	35	GU4	107106	MR11FTE/L	NSP w/Lens	10/200	12	2900	8500	3000	C-6	1-3/8"	10°
MR-11	35	GU4	107108	MR11FTF/L	MFL w/Lens	10/200	12	2900	3000	3000	C-6	1-3/8"	20°
MR-11	35	GU4	107110	MR11FTH/L	FL w/Lens	10/200	12	2900	1500	3000	C-6	1-3/8"	30°
<b>12 VOLT TWIST-LOCK</b>													
MR-11	20	Ba15d	107101	MR11FTB/L/TL	NSP w/ Lens Twist Lock	10/200	12	2900	5500	3000	C-6	1-5/8"	10°
MR-11	20	Ba15d	107103	MR11FTC/L/TL	MFL w/ Lens Twist Lock	10/200	12	2900	1750	3000	C-6	1-5/8"	20°
MR-11	20	Ba15d	107105	MR11FTD/L/TL	FL w/ Lens Twist Lock	10/200	12	2900	700	3000	C-6	1-5/8"	30°
MR-11	35	Ba15d	107456	MR11FTF/L/TL	MF w/ Lens Twist Lock	10/200	12	2900	2200	3000	C-6	1-5/8"	20°
<b>24 VOLT BI-PIN</b>													
MR-11	20	GU4	107476	MR11FTD/L/24V	FL w/ Lens	10/200	24	2900	500	3000	CC-6	1-3/8"	30°
<b>120 VOLT GU10</b>													
MR-11	20	GU10	107544	MR11FL20/L/GU10	FL w/ Lens	10/200	120	2900	220	2000	CC-2	1-7/8"	30°
MR-11	35	GU10	107546	MR11FL35/L/GU10	FL w/ Lens	10/200	120	2900	560	2000	CC-2	1-7/8"	30°