



MSD Platinum (Touring/Stage)

MSD Platinum 5 R UNP/24

The MSD Platinum lamps open up new levels of creative freedom in entertainment lighting, with powerful, compact and brilliantly intense light. Their compact, lightweight design provides the freedom to create smaller, lighter luminaires – for use at any location on stage. And their short arc, high color temperature and innovative reflector produce a sparkling, high beam intensity for outstanding color reproduction. They also offer long and reliable lifetime, high efficacy and fast replacement times. It all adds up to an intensely exciting creative experience.

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General information	
Cap-Base	- [-]
Operating Position	UNIVERSAL [Any or Universal (U)]
Main Application	Stage/Touring
Life to 50% Failures (Nom)	3000 h
System Description	Reflector-E20.6
Light technical	
Color Code	2
Luminous Flux (Min)	7100 lm
Luminous Flux (Nom)	7950 lm
Chromaticity Coordinate X (Nom)	300
Chromaticity Coordinate Y (Nom)	300

Correlated Color Temperature (Nom)	8000 K
Color Rendering Index (Nom)	-
Operating and electrical	
Power (Nom)	189 W
Controls and dimming	
Dimmable	Yes
Mechanical and housing	
Cap-Base Information	-

MSD Platinum (Touring/Stage)

Luminaire design requirements


Pinch Temperature (Max)	350 °C
Pinch Temperature (Max)-DUP(do not use)	350 °C

Product data

Full product code	872790088733400
Order product name	MSD Platinum 5 R UNP/24
EAN/UPC - Product	8727900783506

Order code	928190805308
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	24
Material Nr. (12NC)	928190805308
Net Weight (Piece)	66.500 g

Dimensional drawing



MSD Platinum 5 R UNP/24

Product	D (max)	T (max)	O	C (max)
MSD Platinum 5 R UNP/24	51.4 mm	6.8 mm	1.0 mm	57.1 mm

Photometric data

