

NL-410 / NL-411

4" Round Adjustable Baffle

FEATURES

Trim: Precision spun 0.040 aluminum baffle with deep grooves to reduce aperture glare. Non-reflective painted finishes. Gimbal ring allows lamp to be mounted on top of the trim and adjustable up to 35°. Separate trim ring available in plastic or metal, may also be used with custom combination of ring finishes.

Mounting: Trim includes three trim clips that securely mount trim in housing.

COMPATIBLE HOUSINGS

Compatible with Line Voltage and Low Voltage housings. See individual specification sheets for more information.

COMPATIBLE LAMP / HOUSINGS

Low Voltage:

20W MR16 max. (NL-401QAT/20; NLIC-401QSAT/20; NLR-404QAT/20; NL-402S/20; NLR-403S/20)

37W MR16 max. (NL-401QAT/37; NLIC-401QSAT/37; NLR-404QAT/37; NLR-405AT/37; NLIC-402QSAT/37; NL-402S/37; NLR-403S/37)

50W MR16 max. (NLIC-401AT/1EL; NLIC-401AT/2EL; NLIC-401QSAT; NL-401AT/1EL; NL-401QAT; NLR-404AT/1EL; NLR-404QAT; NL-402S/1EL; NL-402S; NLR-403S/1EL; NLR-403S)

Line Voltage:

20W MR16 max. (NSEIC-407AT/20; NSERIC-407AT/20)

25W MR16 max. (NFBIC-401AT/25A)

50W MR16 GU10 max. (NSL-401AT/10; NSLIC-401AT/10; NSLR-404AT/10)


LABELS AND LISTINGS

cULus Listed for Damp Location when used with compatible housing.



Type	
Project	
Catalog No.	
Notes	

PRODUCT IMAGES AND DIMENSIONS



NL-410
White Baffle
White Trim



NL-410BZ
Bronze Baffle
Bronze Trim



NL-410P
White Phenolic Baffle
White Plastic Trim



NL-411
Black Baffle
White Trim



NL-411B
Black Baffle
Black Trim

Compatible Housings

Catalog No.

Low Voltage

■ **NLIC-401QSAT/20** = ICAT New Construction / 120V Magnetic / 20W max.

■ **NLIC-401QSAT/37** = ICAT New Construction / 120V Magnetic / 37W max.

■ **NLIC-401QSAT** = ICAT New Construction / 120V Magnetic / 50W max.

■ **NLIC-401AT/1EL** = ICAT New Construction / 120V Electronic / 50W max.

■ **NL-401QAT/20** = Non-IC AT New Construction / 120V Magnetic / 20W max.

■ **NL-401QAT/37** = Non-IC AT New Construction / 120V Magnetic / 37W max.

■ **NL-401QAT** = Non-IC AT New Construction / 120V Magnetic / 50W max.

■ **NL-401AT/1EL** = Non-IC AT New Construction / 120V Electronic / 50W max.

■ **NL-402S/20** = Non-IC Shallow New Construction / 120V Magnetic / 20W max.

■ **NL-402S/37** = Non-IC Shallow New Construction / 120V Magnetic / 37W max.

■ **NL-402S** = Non-IC Shallow New Construction / 120V Magnetic / 50W max.

■ **NL-402S/1EL** = Non-IC Shallow New Construction / 120V Electronic / 50W max.

■ **NLR-403S/20** = Non-IC Shallow Remodel / 120V Magnetic / 20W max.

■ **NLR-403S/37** = Non-IC Shallow Remodel / 120V Magnetic / 37W max.

■ **NLR-403S** = Non-IC Shallow Remodel / 120V Magnetic / 50W max.

■ **NLR-403S/1EL** = Non-IC Shallow Remodel / 120V Electronic / 50W max.

■ **NLR-404QAT/20** = Non-IC AT Remodel / 120V Magnetic / 20W max.

■ **NLR-404QAT/37** = Non-IC AT Remodel / 120V Magnetic / 37W max.

■ **NLR-404QAT** = Non-IC AT Remodel / 120V Magnetic / 50W max.

■ **NLR-404AT/1EL** = Non-IC AT Remodel / 120V Electronic / 50W max.

Line Voltage

■ **NSEIC-407AT/20** = ICAT LED New Construction / 20W max.

■ **NSERIC-407AT/20** = ICAT LED Remodel / 20W max.

■ **NFBIC-401AT/25A** = Fire Rated IC Air-Tight New Construction / 25W max.

■ **NSLIC-401AT/10** = ICAT New Construction / 50W max.

■ **NSL-401AT/10** = Non-IC Air-Tight New Construction / 50W max.

■ **NSLR-404AT/10** = Non-IC Air-Tight Remodel / 50W max.

4" Round Adjustable Baffle

Catalog No.

- **NL-410** = White Baffle with White Metal Trim
- **NL-410BZ** = Bronze Baffle with Bronze Metal Trim
- **NL-410P** = White Phenolic Baffle with White Plastic Trim
- **NL-411** = Black Baffle with White Metal Trim
- **NL-411B** = Black Baffle with Black Metal Trim

Example: **NL-410** = 4" Round White Adjustable Baffle with White Metal Ring