

Catalog Number
Notes
Type

## FEATURES & SPECIFICATIONS

### INTENDED USE

Provides years of maintenance-free illumination for indoor or outdoor use in residential & commercial applications.

### CONSTRUCTION

Cast-aluminum housing with corrosion-resistant paint in an industrial grey finish.

Sealed gasket protects against moisture and dust.

### OPTICS

4000K CCT LEDs.

Frosted glass diffuser provides even light distribution.

### LUMEN MAINTENANCE

LEDs will deliver 70% of their initial lumens at 50,000 hour average LED life. See Lighting Facts label on page 2 for performance details.

### ELECTRICAL

MVOLT driver operates on any line voltage from 120-277V

Operating temperature -40°C to 40°C.

4kV surge protection standard.

### INSTALLATION

Mounts to ceiling or wall with surface mount junction box (included).

### LISTINGS

UL Listed to U.S. and Canadian safety standards for wet locations.

Tested in accordance with IESNA LM-79 and LM-80 standards.

### WARRANTY

5-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Full warranty terms located at [www.AcuityBrands.com/CustomerResources/Terms\\_and\\_Conditions.aspx](http://www.AcuityBrands.com/CustomerResources/Terms_and_Conditions.aspx)

Note: Actual performance may differ as a result of end-user environment and application.

All values are design or typical values, measured under laboratory conditions at 25 °C.

Specifications are subject to change without notice.

Outdoor General Purpose

# OLVTCM & OLVTWM




LED VAPORTIGHT



### Specifications

All dimensions are inches (centimeters)



### ORDERING INFORMATION

For shortest lead times, configure products using **bolded options**.

Example: OLVTCM

Series	Color temperature	Voltage	Finish
<b>OLVTCM</b> Ceiling MT	<b>(blank)</b> 4000K	<b>(blank)</b> MVOLT (120V-277V)	<b>(blank)</b> Grey
<b>OLVTWM</b> Wall MT			



Series	System Wattage	Lumens
OLVTCM	15W	600
OLVTWM	15W	600

# OLVTCM & OLVTWM LED Vaportight

## PHOTOMETRICS

To see complete photometric reports or download .ies files for this product, visit Lithonia Lighting's Outdoor LED homepage  
Tested in accordance with IESNA LM-79 and LM-80 standards.

### OLVTCM



### OLVTWM

