
ORIGINAL

Lamps with metal bases



Areas of application

- Position and parking light
- Indicator, brake, fog and reversing lights
- Number plate and side position lights


Product benefits

- OEM Quality
- Wide product range
- Reliable quality


Product features

- Original spare parts


Product family datasheet




Product line drawing




Product line drawing




Product line drawing




Product line drawing




Product line drawing



Product line drawing



Product line drawing



Product line drawing

Product family datasheet

Technical data

Product description	Electrical data					Photometrical data		Dimensions & weight
	Power input	Nominal voltage	Nominal wattage	Power input tolerance	Test voltage	Luminous flux	Luminous flux tolerance	Length
3797	3 W	24.0 V	2.00 W	±15 %	28.0 V	17.5 lm	±30 %	23.9 mm
64138	28 W	24.0 V	21.00 W	±5 %	28.0 V	600 lm	±15 %	38.9 mm
7244	20 W	24.0 V	18/5 W	±6 %	28.0 V	312 lm	±20 %	52.5 mm
7537	28 / 10 W	24.0 V	21/5 W	±6 / ±10 %	28.0 V	440/40 lm	±15 / ±20 %	52.5 mm
7511	28 W	24.0 V	21.00 W	±6 %	28.0 V	460 lm	±15 %	52.5 mm
5637	12.5 W	24.0 V	10.00 W	±10 %	28.0 V	125 lm	±20 %	37.5 mm
5626	7 W	24.0 V	5.00 W	±10 %	28.0 V	50 lm	±25 %	37.5 mm
5627	7 W	24.0 V	5.00 W	±10 %	28.0 V	50 lm	±20 %	37.5 mm
3930	5 W	24.0 V	4.00 W	±10 %	28.0 V	35 lm	±20 %	27.4 mm
7529	15 W	24.0 V	15.00 W	±10 %	28.0 V	210 lm	±25 %	46.5 mm

Product description	Diameter	Lifespan		Additional product data	Certificates & standards	Country specific categorizations
		Lifespan B3	Lifespan Tc	Base (standard designation)	ECE category	Order reference
3797	9 mm	1000 h	2000 h	BA9s	-	3797 2W 24V BA9
64138	9 mm	150 h	400 h	BAY9s	H21W	64138 21W 24V B
7244	25.0 mm			BAY15d	P21/5W	7244 18/5W 24V
7537	27.0 mm	65 / 600 h	600 / 1600 h	BAY15d	P21/5W	7537 21/5W 24V
7511	26.5 mm	200 h	400 h	BA15s	P21W	7511 21W 24V BA
5637	16.0 mm	400 h	800 h	BA15s	R10W	5637 10W 24V BA
5626	16.0 mm	80 h	250 h	BA15d	R5W	5626 5W 24V BA1
5627	16.0 mm	500 h	1000 h	BA15s	R5W	5627 5W 24V BA1
3930	8.8 mm	550 h	1000 h	BA9s	T4W	3930 4W 24V BA9

Product family datasheet

Product description	Diameter	Lifespan		Additional product data	Certificates & standards	Country specific categorizations
		Lifespan B3	Lifespan Tc	Base (standard designation)	ECE category	Order reference
7529	25.0 mm	100 h	300 h	BA15s	-	7529 15W 24V BA

Product family datasheet

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.