



**Product Number:** 59078  
**Order Abbreviation:** 6.6A/200T4Q/64386  
**General Description:** 200 watt, tungsten haloge, current controlled, single ended, airfield

#### Product Information

Abbrev. With Packaging Info.	66A200T4Q64386 40/CS 1/SKU
Application	AIRFIELD/AIRPORT
Average Rated Life (hr)	1200
Base	G6.35 Bipin
Bulb	T13,5
Class	C (GAS)
Color Rendering Index (CRI)	100
Color Temperature (K)	3200
Current (A)	6.6
Diameter d (in)	0.531
Diameter d (mm)	13.50
Distance a (in)	1.299
Distance a (mm)	33
Filament	C BAR 6
Filament Dimensions Length (in)	.271
Filament Dimensions Length (mm)	6.9
Filament Dimensions Width (in)	.177
Filament Dimensions Width (mm)	4.5
Lamp Finish	Clear
Length l1 (in)	1.850
Length l1 (mm)	47
LIF Code	J1/39
Light Center Length - LCL (in)	1.299
Light Center Length - LCL (mm)	33
Luminous Flux (lm)	4700
Maximum Overall Length - MOL (in)	1.850
Maximum Overall Length - MOL (mm)	47
Nominal Wattage (W)	200.00
Operating Position	S 90
Type of Current	AC

#### Footnotes

- s (Operating Position) = Vertical, base down
- p (Operating Position) = Horizontal