

PRODUCT DATASHEET

HALOLINE 1000 W 230 V R7S

HALOLINE Standard | Double ended halogen lamps with tube base



AREAS OF APPLICATION

- Ideal for emphasizing and accentuating buildings
- General illumination
- Entrance lighting
- Pathway lighting
- Garden lighting
- Traffic areas
- Shops
- Restaurants, hotels and similar prestigious applications
- Outdoor applications only in suitable luminaires

PRODUCT BENEFITS

- Brilliant accent light
- No transformer required
- Contains no mercury

PRODUCT FEATURES

- Average life: 2,000 h
- 100 % dimmable
- Color rendering index R_a : 100
- Color temperature: 3,000 K
- Burning position: p15

TECHNICAL DATA

Electrical data

Nominal wattage	1000.00 W
Nominal voltage	230 V
Rated wattage	1000.00 W
Power factor λ	1.00
Claimed equiv. conventional lamp power	1000 W

Photometrical data

Rated color temperature	2900 K
Light color (designation)	Warm White
Rated luminous flux	22000 lm
Color rendering index Ra	100
Lumen main.fact.at end of nom.life time	0.80
Color temperature	2900 K
Luminous flux	22000 lm
Color rendering index Ra	100
Nominal luminous flux	22000 lm

Light technical data

Starting time	0.0 s
Warm-up time (60 %)	0.00 s

Dimensions & weight



Diameter	12.0 mm
Overall length	185.7 mm
Length	191.1 mm
Outer bulb	T12
Maximum diameter	12.0 mm

Lifespan

Nominal lamp life time	2000 h
Rated lamp life time	2000 h
Number of switching cycles	50000

Additional product data

Base (standard designation)	R7s
Mercury content	0.0 mg
Mercury-free	Yes
Product remark	Fuse protection with indicated values recommended acc. to IEC60357, EN60357/For outdoor applications and operation in damp locations special approved fixtures are required

Capabilities

Burning position	p15
Fuse, quick-acting	6.3 A
Dimmable	Yes


Certificates & standards

Energy efficiency class	C
Energy consumption	1000 kWh/1000h
Energy efficiency class	C

Country-specific categorizations

ILCOS	HDG-1000-230-R7s-191,1
-------	------------------------

Light Distribution



Spectral power distribution

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300004174	HALOLINE 1000 W 230 V R7S	Shipping carton box 12	245 mm x 85 mm x 112 mm	2.33 dm ³	352.20 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.