



Product Number: 65851

Order Abbreviation: PANELRDORKIT2A35UNHD8SC722WH

General Description: Backlit Panel Doorkit Dual 2A compatible with most fluorescent troffers, 2200/3300/3850lm, 20,30, or 35W, 110lm/W, 3-CCT Selectable 3500/4000/5000K, 0-10V Dimable,120-347V, 80CRI, 2x2, 50,000 lifetime.

Product Information

Power Factor	0.90
Total Harmonic Distortion (THD)	< 20 %
Efficacy (LPW)	110 lm/W
Operating Voltage (V)	120
Abbrev. With Packaging Info.	PANELRDORKIT2A35UNHD8SC722WH 2/CS 2/SKU
Ordering Abbreviation	PANELRDORKIT2A35UNHD8SC722WH
Average Rated Life 1 (hr)	50000
Nominal Wattage (W)	35.00
UPC Code	UPC046135658518
Color Rendering Index (CRI)	80
Service Life Rating	50000
Lumens (lm)	2200
Color Temperature/CCT (K)	3500
Connectors	not relevant
Fixture Warranty	5 years
Housing	Aluminum
Luminaire Finish	White
Luminaire Type	Panel
Maximum Operating Temperature-Celsius	45
Mounting	Recessed
Certification Listing	RoHS,FCC,cETLus
Height (in)	2.409 in
Height (mm)	61.20 mm
Nominal Length (inch)	22.126 in
Width (in)	21.46 in
Width (mm)	545.00 mm
Product Weight (g)	4100.00