



23105 Kashiwa Court, Torrance, CA 90505
Phone: (800) 579-4875 or (310) 534-1505 Fax: (310) 534-1424
E-mail: info@ledtronics.com
Website: <http://www.ledtronics.com>

PAR30C-12WC-XPW-101M

LED SpotLight, Par30, Clear, 12W, E26 Base
100~277Vac, Pure White, 5000K
Angle of illumination: 50°



DWG BY:
KTC / GP
06-10-19

R&D:
UF
09-09-19

MFG:
LD
09-09-19

QA:
SB
09-09_-19

REVISION LTR: A
ECR#: 090619-UF01
09-09-19

○ **Features**

Operating Temperature	-30°C to +55°C
Storage Temperature	-40°C to +80°C
Heatsink Temperature	60°C
Heatsink Material / Color	Cold Forged Aluminum / Gray
Body Material / Color	Polycarbonate / White
Lens Material / Color	Polycarbonate / Clear-Prismatic
ETL Listed	KING-PAR30-COB
LED LM80 Report	-
LM79 Report	-
Protection Rating	IP41
LED Type	COB
Dimmable	No
Lifespan	50,000 hrs.
Warranty	5 Years
Weight	0.42 lbs.


 ○ **Electro-Optical Characteristics**

Part Number	PAR30C-12WC-XPW-101M
Input Voltage (typ)	100~277Vac
Tested @ (Voltage)	120Vac
Power Consumption	11.5W
Current Consumption	0.099 A
Efficacy: (Lm/W)	122
Lumens	1402 lm
Max Ft-Cd	2694 cd
Power Factor	0.97
CRI (Ra)	80
CCT	5000K
Color	Pure White
Angle of illumination	50°

○ **Dimensions**



Tolerance:
XXX +/- .010
XX +/- .025

Notes:
1. All Dimensions are in Inches [Millimeters].