

PAR36-5W-TPW-014W

PAR36 LED Floodlight, Screw Terminal
12/14Vdc, True White, 5000K
Angle of illumination: 120° x 105°



DWG BY:
GP
06-01-16

CHK BY:
PL
06-03-16

R&D:
LUV
06-02-16

REVISION LTR: -

06-01-16

○ **Features**

Operating Temperature	-20°C to +40°C
Base Material	Polycarbonate
Base Color	Black
Lens Material	Polycarbonate
Lens Color	Clear
LED LM80 Report	-
LM79 Report	-
Dimmable	No
Life Span	50,000 hrs.
Warranty	3 Years
Weight	0.2 lbs.



○ **Electro-Optical Characteristics**

Part Number	PAR36-5W-TPW-014W
Input Voltage (typ)	12/14Vdc
Tested @ (Voltage)	14Vdc
Power Consumption	4.5W
Current Consumption	0.330 A
Efficacy: (Lm/W)	100
Lumens	460 lm
Max Ft-Cd	165 cd
Power Factor	-
CRI (Ra)	75
CCT	5000K~6000K
Color	True White
Angle of illumination	120° x 105°

○ **Dimensions**



Notes:

1. All Dimensions are in Inches [Millimeters].

Tolerance:

- XXX +/- .010
- XX +/- .025